

PRODUCT-DETAILS

AF12ZB-30-01RT-21

AF12ZB-30-01RT-21 24-60V50/60HZ 20-60VDC Contactor



General Information

Extended Product Type	AF12ZB-30-01RT-21
Product ID	1SBL156060R2101
EAN	3471523128019
Catalog Description	AF12ZB-30-01RT-21 24-60V50/60HZ 20-60VDC Contactor
Long Description	The AF12ZB-30-01RT-21 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and Ring-Tongue Terminals, controlling motors up to 5.5 kW / 400 V AC (AC-3) or 7-1/2 hp / 480 V UL and switching power circuits up to 28 A (AC-1) or 28 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (24-60 V 50/60 Hz and 20-60 V DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Instructions and Manuals	1SBC101035M6801
--------------------------	-----------------

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	77 mm
Product Net Height	86 mm
Product Net Weight	0.32 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011, IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives.
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 35 A acc. to IEC 60947-5-1, $q = 40^\circ\text{C}$ 16 A
Rated Operational Current AC-1 (I_e)	(690 V) 40°C 28 (690 V) 60°C 28 A (690 V) 70°C 24
Rated Operational Current AC-3 (I_e)	(415 V) 60°C 12 A (440 V) 60°C 12 A (500 V) 60°C 12.5 A (690 V) 60°C 9 A (380 / 400 V) 60°C 12 A (220 / 230 / 240 V) 60°C 12 A
Rated Operational Power AC-3 (P_e)	(415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW
Rated Operational Current AC-15 (I_e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current (I_{cw})	at 40°C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40°C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40°C Ambient Temp, in Free Air, from a Cold State 30 s 80 A for 0.1 s 140 A for 1 s 100 A
Maximum Breaking Capacity	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 250 A $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 106 A
Maximum Electrical Switching Frequency	(AC-1) 600 cycles per hour (AC-15) 1200 cycles per hour (AC-2 / AC-4) 300 cycles per hour (AC-3) 1200 cycles per hour (DC-13) 900 cycles per hour
Rated Operational Current DC-13 (I_e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W

	(220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Insulation Voltage (U _i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Maximum Mechanical Switching Frequency	3600 cycles per hour
Rated Control Circuit Voltage (U _c)	50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V
Operate Time	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Terminal Type	Ring-Tongue Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 28 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 1 hp (200 ... 208 V AC) Three Phase 3 hp (220 ... 240 V AC) Three Phase 3 hp (240 V AC) Single Phase 2 hp (440 ... 480 V AC) Three Phase 7-1/2 hp (550 ... 600 V AC) Three Phase 10 hp

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C Close to Contactor without Thermal O/L Relay -40 ... +70 °C Close to Contactor for Storage -60 ... +80 °C
Climatic Withstand	Category B according to IEC 60947-1 Annex Q
Maximum Operating Altitude Permissible	3000 m
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_SE-96551
CCC Certificate	CCC_2010010304445624
CQC Certificate	CQC2010010304445624
Declaration of Conformity - CCC	2020980304001253
Declaration of Conformity - CE	1SBD250004U1000
EAC Certificate	EAC_RU C-FR ME77 B03597
Environmental Information	1SBD250165E1000
Instructions and Manuals	1SBC101035M6801
RoHS Information	1SBD250004U1000
UL Certificate	UL_20121122-E312527_9_5
UL Listing Card	UL_E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	87 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.32 kg
Package Level 1 EAN	3471523128019
Package Level 2 Units	box 27 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	315 mm
Package Level 2 Gross Weight	17.28 kg
Package Level 3 Units	1296 piece

Classifications		
Object Classification Code		Q
ETIM 4	EC000066 - Magnet contactor, AC-switching	
ETIM 5	EC000066 - Magnet contactor, AC-switching	
ETIM 6	EC000066 - Power contactor, AC switching	
ETIM 7	EC000066 - Power contactor, AC switching	
eClass		V11.0 : 27371003
UNSPSC		39121529

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

