

PRODUCT-DETAILS

316MVS5WH

Switched interlocked socket-outlet, vertical,
Heavy Duty, 5h, 16A, IP67, 3P+E



General Information

| | |
|-----------------------|--|
| Extended Product Type | 316MVS5WH |
| Product ID | 2CMA163263R1000 |
| EAN | 7392696632638 |
| Catalog Description | Switched interlocked socket-outlet, vertical, Heavy Duty, 5h, 16A, IP67, 3P+E |
| Long Description | Switched Interlocked Socket Outlet, vertical, Heavy Duty, earthing sleeve position 5h, rated current 16A, IP67 watertight, 3-poles+earth |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Sweden) | E2417138 |
| E-Number (Finland) | 2417138 |
| E-Number (Norway) | 2417138 |
| EAN | 7392696632638 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|---------------------|-----------------|
| Product Net Width | 160 mm |
| Product Net Height | 205 mm |
| Product Net Weight | 1.83 kg |
| Mechanical Drawings | 9AKK107991A3927 |

Container Information

| | |
|--------------------------------|------------------------|
| Package Level 1 Width | 215 mm |
| Package Level 1 Depth / Length | 335 mm |
| Package Level 1 Height | 165 mm |
| Package Level 1 Gross Weight | 1.83 kg |
| Package Level 1 EAN | 7392696632638 |
| Package Level 1 Units | box 1 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 96.86 kg |
| Package Level 2 EAN | 7392696068321 |
| Package Level 2 Units | pallet (lift) 42 piece |

Environmental

| | |
|-------------|---|
| RoHS Status | Following EU Directive 2011/65/EU |
| SCIP | Czech Republic - 8f2a459d-ae21-4edc-8431-c56a61d9e5ef |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000057M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 2CHC660004X0203 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|--|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 1.5 ... 4 mm ² |
| Cable Diameter | 13 ... 17 mm |
| Cable Entry Position | Knock-out on Top and drill marks down |
| Cable Outlets Per Side | 1xØ40+1xØ50 mm on top and drill marks on bottom |
| Color | Black |
| Connection Type | Screw |
| Degree of Protection | IP67 IP69 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Switched Interlocked Socket outlet, vertical, Heavy Duty |
| Housing Material | Thermoplastic (PBT) |
| Invoice Description | IND. P&S#316MVS5WH |
| Mounting Holes | 130x225 |
| Mounting Type | Vertical |
| Number of Poles | 4 |

| | |
|----------------------------|---|
| Order Multiple | 1 piece |
| Product Main Type | CMVS |
| Product Name | Industrial Switched Interlocked Socket Outlet |
| Protection Type | Switched Interlocked |
| Rated Current (I_n) | 16 A |
| Rated Voltage (U_r) | 600 ... 690 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2, -4 |
| Suitable For | Switched Interlocked Socket Outlets, Vertical |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC000029M0001 |
| Installation Manual | 2CMC000029M0001 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 14 ... 12 AWG |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

