

---

PRODUCT-DETAILS

# FC-S5/250 230V-9h

## Ind. P&S#FC-S5/250 230V-9h




---

### General Information

Extended Product Type	FC-S5/250 230V-9h
Product ID	2CMA103314R1000
EAN	7392696033145
Catalog Description	Ind. P&S#FC-S5/250 230V-9h
Long Description	Industrial connectors, 3P+N+E, IP67, 250 A, 200 ... 250 V, The compact C-Line connectors have a robust plastic housing and are perfect for applications with limited space conditions as well as for certain industries (chemistry, food industry). Designed for high temperature.

---

### Ordering

EAN	7392696033145
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

---

### Dimensions

Product Net Width	190 mm
Product Net Height	185 mm
Product Net Weight	3.6 kg

---

**Container Information**


---

Package Level 1 Width	407 mm
Package Level 1 Depth / Length	407 mm
Package Level 1 Height	187 mm
Package Level 1 Gross Weight	3.6 kg
Package Level 1 EAN	7392696033145
Package Level 1 Units	box 1 piece

---



---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

---



---

**Additional Information**


---

Additional Information	3P+N+E
Ambient Temperature	-40 ... 100 °C
Cable Diameter	45 ... 65 mm
Cable Entry Position	Anti-kink sleeve
Color	Blue
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic
Invoice Description	Ind. P&S#FC-S5/250 230V-9h
Number of Poles	5
Order Multiple	1 piece
Product Main Type	FC
Product Name	High current connector
Protection Type	Splashproof
Rated Current ( $I_n$ )	250 A
Rated Voltage ( $U_r$ )	120/208 ... 144/250 V
Standards	IEC 60309-1, -2
Sub-Function	C-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

---



---

**Classifications**


---

eClass	27440509
UNSPSC	39120000

---

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

