

PRODUCT-DETAILS

MCP-S5/250 400V-6h

Ind. P&S#MCP-S5/250 400V-6h



General Information

Extended Product Type	MCP-S5/250 400V-6h
Product ID	2CMA103205R1000
EAN	7392696032056
Catalog Description	Ind. P&S#MCP-S5/250 400V-6h
Long Description	Panel mounted inlet, 3P+N+E, IP67, 250 A, 200/346 ... 240/415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connectors also suitable for marine applications. Aluminum housing. Designed for high temperature.

Ordering

EAN	7392696032056
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	230 mm
Product Net Height	350 mm

Product Net Weight	8.6 kg
--------------------	--------

Container Information

Package Level 1 Width	277 mm
Package Level 1 Depth / Length	277 mm
Package Level 1 Height	352 mm
Package Level 1 Gross Weight	8.6 kg
Package Level 1 EAN	7392696032056
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 100 °C
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Aluminum
Invoice Description	Ind. P&S#MCP-S5/250 400V-6h
Mounting Holes	155x155
Number of Poles	5
Order Multiple	1 piece
Product Main Type	MCP
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	250 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9007 - Grey Aluminium

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

