


PRODUCT-DETAILS

216QP6W

Ind. P&S#216QP6W



General Information

Extended Product Type	216QP6W
Product ID	2CMA102296R1000
EAN	7392696022965
Catalog Description	Ind. P&S#216QP6W
Long Description	Plug, earthing sleeve position 6h, rated current 16A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Blue, Screwless terminals

Ordering

E-Number (Sweden)	E2404983
EAN	7392696022965
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	72 mm
Product Net Height	72 mm
Product Net Weight	0.167 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.853 kg
Package Level 1 EAN	7392696037723
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Diameter	6 ... 16 mm
Cable Entry Position	Swivel
Color	Blue
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216QP6W
Number of Poles	3
Order Multiple	10 piece
Product Main Type	QP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I _n)	16 A
Rated Voltage (U _r)	200 ... 250 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

