

PRODUCT-DETAILS

TBFP9-2

SMOOTH FILLER/PUTTY WHT 1 IN X 25IN



General Information

Extended Product Type	TBFP9-2
Product ID	7TBA017450R0002
EAN	0786210978697
Catalog Description	SMOOTH FILLER/PUTTY WHT 1 IN X 25IN
Long Description	Smooth Filler/Putty Compound, 1 Inch X 25 Inch, White, Material - Modified Silicone Rubber Compound. Tensile Strength 1200 psi, Dielectric Strength 20 mil - 600 vpm, 40 mil - 400 vpm. Abrasion Resistance - 110 pounds/inch, Water Absorption less than 0.5 percent. Temperature Rating 80 Degrees C, Voltage Rating 600 Volts max.

Ordering

EAN	0786210978697
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	40 piece
Package Level 2 Width	11.25 in 286 mm

Package Level 2 Height	17 in 432 mm
Package Level 2 Depth / Length	11.25 in 286 mm

Additional Information

Application	Repair deteriorated insulation on cables and conductors. Insulate and seal underwater, underground and above-ground bonding installations.
Brand / Label	Shrink-Kon
Effective Date	20050907
Material	Modified silicone rubber compound
Number of Batteries	0
Product Name	SILICONE RUBBER SMOOTH FILLER/PUTTY
Product Type	Splice Insulators and Insulating Covers
Special Functions	Smooth filler putty compound available for use under tape when insulating bolted or dimensionally inconsistent splices and terminations.
UPC	786210978697
Voltage Rating	600 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TBFP9-2
Instructions and Manuals	TBFP9-2

Classifications

ETIM 6	EC000219 - Repair seal
ETIM 7	EC000219 - Repair seal
UNSPSC	39121721
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5069 >> Electrical insulators

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

