

PRODUCT-DETAILS

# OT250KAUC6AZ

## OT250KAUC6AZ Safety switch



### General Information

Extended Product Type	OT250KAUC6AZ
Product ID	1SCA022542R6300
EAN	6417019171258
Catalog Description	OT250KAUC6AZ Safety switch

### Long Description

The enclosed switch is using a galvanised steel enclosure, with polyester coating. It is suitable for outdoor use with respect to UV light and ingress protection. The enclosure have inbuilt gas pressure relief function to protect the user in case of an internal arc. The door is earthed via the hinges. The enclosure is prepared for single and parallell cables. Cable entry types can be blank , ring-flange or C-flange type (FL21), with different cable configuration, like top/bottom or bottom/bottom. The handle is padlockable for 3 padlocks, cover is interlocked, and interlock function can be bypassed for thermographing.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85363090
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC340015C0201
-----------------------------------	-----------------

Instructions and Manuals

1SCC340005M0007

Mechanical Drawings

OTKM808023PBL4C.stp

## Dimensions

Product Net Width	800 mm
Product Net Height	800 mm
Product Net Depth / Length	230 mm
Product Net Weight	21.14 kg

## Technical

Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 132 kW (500 V) 160 kW (690 V) 200 kW
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 1000 V
Rated Operational Voltage	Main Circuit 1000 V
Rated Short-Circuit Making Capacity ( $I_{cm}$ )	(1000 V AC) 30 kA
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 8 kA
Power Loss	at Rated Operating Conditions per Pole 6.5 W
Pollution Degree	3
Handle Color	Red / Yellow
Handle Type	Pistol handle
Standards	IEC 60947-1, -3
Number of Poles	6
Connecting Capacity Main Circuit	Hole Diameter 8 mm Screw Clamp / PE Terminal 8pcs, 25...120 mm <sup>2</sup>
Cable Entry Position	Down/Down
Cable Outlets Per Side	Blank / 4xC-flange, Knock-outs: 2x10mm, 12.5mm, 20.5mm, 25.5mm, 32.5mm
Degree of Protection	acc. to IEC 60529 IP65
Enclosure Material	Steel sheet
Maximum Mounted Auxiliary Contacts	4 NO, 2 NC
Mounted Auxiliary Contacts	4 NO, 2 NC

---

## Environmental

---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

## Certificates and Declarations (Document Number)

---

Declaration of Conformity - CE	1SCC340025D2704
Instructions and Manuals	1SCC340005M0007
RoHS Information	1SCC340049D0202

---



---

## Container Information

---

Package Level 1 Units	box 1 piece
Package Level 1 Width	815 mm
Package Level 1 Depth / Length	910 mm
Package Level 1 Height	325 mm
Package Level 1 Gross Weight	25 kg
Package Level 1 EAN	6417019171258

---



---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

---



---

## Categories

---

Low Voltage Products and Systems → Enclosed Switches → Enclosed Safety Switches → Enclosed Safety Switches

