

## PRODUCT-DETAILS

# BC6-30-10-P-16

## BC6-30-10-P-16 Mini Contactor 48VDC



### General Information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | BC6-30-10-P-16                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Product ID            | GJL1213009R1106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| EAN                   | 4013614162718                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Catalog Description   | BC6-30-10-P-16 Mini Contactor 48VDC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Long Description      | The BC6-30-10-P mini contactor is a compact 3 pole contactor with 1 auxiliary contact and soldering pins. They are ideally suited for applications where reliability is a must and space is at a premium. Mini contactors are used in residential buildings, commercial buildings and industrial applications for the control of single or three-phase loads up to 4 kW (AC-3) and 20 A / 690 V (AC-1) or switching of control signals. Further features are the noiseless and hum-free coil and a switch position indication. |

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85365080 |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SBC100214C0201 |
| Instructions and Manuals          | 2CDC102047M6801 |
| Dimension Diagram                 | GJL1200438F0001 |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 47.5 mm |
| Product Net Height         | 45.5 mm |
| Product Net Depth / Length | 51.5 mm |
| Product Net Weight         | 0.17 kg |

## Technical

|                                                    |                                                                                                                                                        |
|----------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Poles                                    | 3                                                                                                                                                      |
| Mini Contactor Type                                | Mini Contactor                                                                                                                                         |
| Rated Operational Voltage                          | Auxiliary Circuit 690 V AC<br>Auxiliary Circuit 250 V DC<br>Main Circuit 690 V AC<br>Main Circuit 220 V DC                                             |
| Rated Frequency (f)                                | Control Circuit DC<br>Main Circuit 60 Hz<br>Main Circuit 50 Hz<br>Main Circuit DC                                                                      |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | Auxiliary Circuit 6 kV<br>Main Circuit 6 kV                                                                                                            |
| Rated Insulation Voltage ( $U_i$ )                 | 690 V<br>acc. to UL/CSA 600 V                                                                                                                          |
| Number of Main Contacts NC                         | 0                                                                                                                                                      |
| Number of Main Contacts NO                         | 3                                                                                                                                                      |
| Rated Operational Current AC-1 ( $I_e$ )           | (220 / 240 V) 40 °C 12 A<br>(220 / 240 V) 55 °C 12 A<br>(380 / 440 V) 40 °C 12 A<br>(380 / 440 V) 55 °C 12 A<br>(690 V) 40 °C 6 A<br>(690 V) 55 °C 6 A |
| Rated Operational Power AC-3 ( $P_e$ )             | (230 V) Three Phase 2.2 kW<br>(400 V) Three Phase 4 kW<br>(500 V) Three Phase 4 kW<br>(690 V) Three Phase, NO 3 kW                                     |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 64 A                                                                                        |
| Number of Auxiliary Contacts NC                    | 0                                                                                                                                                      |
| Number of Auxiliary Contacts NO                    | 1                                                                                                                                                      |
| Rated Operational Current AC-15 ( $I_e$ )          | (24 V) 4 A<br>(120 V) 4 A<br>(500 V) 2 A<br>(220 / 240 V) 4 A<br>(380 / 400 V) 3 A                                                                     |
| Rated Operational Current DC-13 ( $I_e$ )          | (24 V) 2.5 A<br>(110 V) 0.7 A<br>(220 / 240 V) 0.4 A                                                                                                   |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | Main Circuit 12 A                                                                                                                                      |
| Rated Control Circuit Voltage ( $U_c$ )            | 48 V DC                                                                                                                                                |
| Coil Operating Limits                              | (acc. to IEC 60947-4-1) for DC supply 0.85 ... 1.1 x $U_c$ (at $\theta \leq 55$ °C)                                                                    |
| Degree of Protection                               | Auxiliary Circuit Terminals IP20<br>Control Circuit Terminals IP20<br>Main Circuit Terminals IP20                                                      |
| Mechanical Durability                              | 10000000 cycle                                                                                                                                         |
| Minimum Switching Capacity                         | Auxiliary Circuit 17 V<br>Auxiliary Circuit 5 mA                                                                                                       |
| Maximum Electrical Switching Frequency             | (AC-1) 300 cycles per hour<br>(AC-15) 600 cycles per hour                                                                                              |

|                      |                                                                                                                       |
|----------------------|-----------------------------------------------------------------------------------------------------------------------|
|                      | (AC-3) 600 cycles per hour<br>(DC-1) 600 cycles per hour<br>(DC-13) 600 cycles per hour<br>(DC-3) 600 cycles per hour |
| Mounting on DIN Rail | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715        |
| Power Loss           | at Rated Operating Conditions per Pole 2 W                                                                            |
| Standards            | IEC/EN 60947-1<br>IEC/EN 60947-4-1<br>IEC/EN 60947-5-1<br>UL 60947-1<br>UL 60947-4-1                                  |

## Technical UL/CSA

|                                  |                                                                                                                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Maximum Operating Voltage UL/CSA | Auxiliary Circuit 600 V AC/DC<br>Main Circuit 600 V AC                                                                                                                                                                 |
| Full Load Amps Motor Use         | (115 V AC) Single Phase 5.8 A<br>(200 V AC) Three Phase 4.8 A<br>(220 ... 240 V AC) Three Phase 6.8 A<br>(230 V AC) Single Phase 4.9 A<br>(440 ... 480 V AC) Three Phase 4.8 A<br>(550 ... 600 V AC) Three Phase 1.7 A |
| Horsepower Rating UL/CSA         | (115 V AC) Single Phase 0.25 Hp<br>(200 V AC) Three Phase 1 Hp<br>(220 ... 240 V AC) Three Phase 2 Hp<br>(230 V AC) Single Phase 0.5 Hp<br>(440 ... 480 V AC) Three Phase 3 Hp<br>(550 ... 600 V AC) Three Phase 1 Hp  |
| General Use Rating UL/CSA        | (300 V AC) 8 A                                                                                                                                                                                                         |

## Environmental

|                                                |                                                    |
|------------------------------------------------|----------------------------------------------------|
| Ambient Air Temperature                        | Operation -25 ... +55 °C<br>Storage -40 ... +80 °C |
| Maximum Operating Altitude Permissible         | 2000 m                                             |
| Resistance to Shock acc. to IEC 60068-2-27     | 11 ms Pulse 15g                                    |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 5 ... 150 Hz                                  |
| RoHS Status                                    | Following EU Directive 2011/65/EU                  |

## Certificates and Declarations (Document Number)

|                                 |                     |
|---------------------------------|---------------------|
| BV Certificate                  | 1SAA920000-0204     |
| CB Certificate                  | 1SAA938000-2002     |
| CQC Certificate                 | CQC2003010304064033 |
| cULus Certificate               | cUL_E191658         |
| Declaration of Conformity - CCC | 2020980304001854    |
| Declaration of Conformity - CE  | 1SAD938516-0001     |
| DNV GL Certificate              | 1SAA938000-0306     |
| EAC Certificate                 | 1SAA920000-2702     |
| Environmental Information       | 1SAC200067H0009     |
| Instructions and Manuals        | 2CDC102047M6801     |
| KC Certificate                  | 1SAA938000-1501     |
| LR Certificate                  | 1SAA938000-0504     |
| RMRS Certificate                | 1SAA938000-0704     |
| RoHS Information                | 1SAD938516-0001     |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 10 piece      |
| Package Level 1 Width          | 108 mm        |
| Package Level 1 Height         | 69 mm         |
| Package Level 1 Depth / Length | 247 mm        |
| Package Level 1 Gross Weight   | 1.775 kg      |
| Package Level 1 EAN            | 4013614415159 |

## Classifications

|                            |                                           |
|----------------------------|-------------------------------------------|
| Object Classification Code | Q                                         |
| ETIM 4                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                     | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                     | EC000066 - Power contactor, AC switching  |
| ETIM 7                     | EC000066 - Power contactor, AC switching  |
| eClass                     | V11.0 : 27371003                          |
| UNSPSC                     | 39121529                                  |

## Accessories

| Identifier      | Description                 | Type      | Quantity | Unit Of Measure |
|-----------------|-----------------------------|-----------|----------|-----------------|
| GJL1201319R0003 | CA6-11M-P Auxiliary Contact | CA6-11M-P | 1        | piece           |
| GJL1201319R0004 | CA6-11N-P Auxiliary Contact | CA6-11N-P | 1        | piece           |
| GJL1201319R0002 | CA6-11E-P Auxiliary Contact | CA6-11E-P | 1        | piece           |

## Categories

Low Voltage Products and Systems → Control Products → Contactors → Mini Contactors

