


PRODUCT-DETAILS

A23

A23 Wall Cabinet 2PW3R PC2 IP44



General Information

Extended Product Type	A23
Product ID	2CPX052011R9999
EAN	4011617520115
Catalog Description	A23 Wall Cabinet 2PW3R PC2 IP44
Long Description	Wall-mounting cabinet, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP44, rated current 250 A, powder-coated, in RAL 9016, enclosure out of sheet steel, metal door , door out of sheet steel, door opening angle 120 degree, cable entry on top via membrane flange mounted, on side via flange opening pre-punched, dimensions in mm (H x W x D): 500 x 550 x 215, Grid unit 3 GU, panel width 2, Space units 72, pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame

Ordering

EAN	4011617520115
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	550 mm
Product Net Height	500 mm

Product Net Depth / Length	215 mm
Product Net Weight	9.888 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	570.000 mm
Package Level 1 Height	520.000 mm
Package Level 1 Depth / Length	233.000 mm
Package Level 1 Gross Weight	10.284 kg
Package Level 1 EAN	4011617520115
Package Level 2 Units	pallet (lift) 21 piece
Package Level 2 Width	800.000 mm
Package Level 2 Height	1750.000 mm
Package Level 2 Depth / Length	1200.000 mm
Package Level 2 Gross Weight	227.648 kg

Additional Information

Color	traffic white
Configuration Type	pre-assembled for installation of metering-, modules, Combi-Sets, CombiLine-Module on EDF-mounting frame
Cover Plate Type	Door
Degree of Protection	IP44
DIN Place Units	72
Enclosure Type	Wall-mounting cabinet
Field Width	2
Housing Material	Steel plate/plastic
Interior Depth	190 mm
Mounting Type	Surface mounted/recessed mounted/partially recessed mounted
Number of Rows	3
Power Loss	$\Delta t = 20K$ 47.2 W $\Delta t = 25K$ 62.3 W $\Delta t = 30K$ 78.1 W
Product Main Type	ComfortLine A
Product Name	A23 Wall Cabinet 2PW3R PC2 IP44
Protection Class	Isolated
Rated Current (I_n)	250 A
Surface Finishing	Powder coating

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	9AKK107680A4773
Instructions and Manuals	2CPC133150M5601

Classifications	
ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories
Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Meter Boards → ComfortLine A
Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Sub Distribution Boards → ComfortLine A

