

PRODUCT-DETAILS

432RS6B

Surface socket outlets, 3P+N+E, 32 A, 200/346
... 240/415 V



General Information

| | |
|-----------------------|---|
| Extended Product Type | 432RS6B |
| Product ID | 2CMA101026R1000 |
| EAN | 7392696010269 |
| Catalog Description | Surface socket outlets, 3P+N+E, 32 A, 200/346 ... 240/415 V |
| Long Description | Surface socket outlets, 3P+N+E, IP44, 32 A, 200/346 ... 240/415 V |

Ordering

| | |
|------------------------|---------------------|
| E-Number (Finland) | 2420321 |
| E-Number (Norway) | 1543470 |
| EAN | 7392696010269 |
| Country of Origin | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece |

Dimensions

| | |
|---------------------|-----------------|
| Product Net Width | 85 mm |
| Product Net Height | 121 mm |
| Product Net Weight | 0.35 kg |
| Mechanical Drawings | 9AKK107680A0706 |

Container Information

| | |
|--------------------------------|-------------------------|
| Package Level 1 Width | 175 mm |
| Package Level 1 Depth / Length | 428 mm |
| Package Level 1 Height | 188 mm |
| Package Level 1 Gross Weight | 3.5 kg |
| Package Level 1 EAN | 7392696014274 |
| Package Level 1 Units | box 10 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 1420 kg |
| Package Level 2 EAN | 7392696065276 |
| Package Level 2 Units | pallet (lift) 400 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1613211 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|------------------------|---|
| Additional Information | 3P+N+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 2.5 ... 10 mm ² |
| Cable Diameter | 22 mm |
| Cable Entry Position | Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry. |
| Color | Red |
| Connection Type | Screw |
| Cover Color | Black |
| Degree of Protection | IP44 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Outlet |
| Housing Material | Plastic (PA) |

| | |
|----------------------------|----------------------------------|
| Invoice Description | IND. P&S#432RS6B |
| Mounting Holes | 111x72 |
| Number of Poles | 5 |
| Order Multiple | 10 piece |
| Product Main Type | ERS |
| Product Name | Wall mounted socket |
| Protection Type | Splashproof |
| Rated Current (I_n) | 32 A |
| Rated Voltage (U_r) | 200/346 ... 240/415 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |
| Installation Manual | 2CMC700014C0016 |
| RAL Number | RAL 9005 - Jet Black |

Classifications

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 12 ... 10 AWG |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

