

PRODUCT-DETAILS

# XT4H 250 Ekip I In=250A 4p F F

# XT4H 250 Ekip I In=250A 4p F F



## General Information

|                       |   |
|-----------------------|---|
| Extended Product Type | XT4H 250 Ekip I In=250A 4p F F  |
| Product ID            | 1SDA068540R1  |
| EAN                   | 8015644024468   |
| Catalog Description   | XT4H 250 Ekip I In=250A 4p F F  |
| Long Description      | C.BREAKER TMAX XT4H 250 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-I R 250 A |

## Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 8015644024468 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362090      |

## Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 140 mm  |
| Product Net Height         | 160 mm  |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight         | 3.05 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Units          | 1 piece       |
| Package Level 1 Width          | 145 mm        |
| Package Level 1 Height         | 210 mm        |
| Package Level 1 Depth / Length | 168 mm        |
| Package Level 1 Gross Weight   | 3.5 kg        |
| Package Level 1 EAN            | 8015644024468 |

## Environmental

RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

## Additional Information

|   |   |
|---|---|
| Circuit Breaker Type to be Associated                       | Power Distribution  |
| Current Type  | AC  |
| Electrical Durability                                       | 120 cycles per hour<br>8000 cycle   |
| Mechanical Durability                                       | Nr. Operations 240 cycles per hour<br>Nr. Operations 25000 cycle  |
| Number of Poles   | 4   |
| Opening Time  | CB with SOR 15 ms<br>CB with UVR 15 ms  |
| Order Multiple  | 1 piece   |
| Product Main Type   | SACE Tmax XT  |
| Product Name  | Moulded Case Circuit Breaker  |
| Product Type  | CB  |
| Rated Current ( $I_n$ )                                     | 250 A   |
| Rated Frequency (f)   | 50 / 60 Hz  |
| Rated Voltage ( $U_r$ )                                     | 690 V   |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )               | 8 kV  |
| Rated Insulation Voltage ( $U_i$ )                          | 1000 V  |
| Rated Operational Voltage                                   | 690 V AC  |
| Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )  | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 45 kA<br>(690 V AC) 15 kA |
| Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ ) | (220 V AC) 100 kA<br>(230 V AC) 100 kA<br>(240 V AC) 100 kA<br>(380 V AC) 70 kA<br>(415 V AC) 70 kA<br>(440 V AC) 65 kA<br>(500 V AC) 50 kA<br>(525 V AC) 45 kA<br>(690 V AC) 15 kA |
| Rated Uninterrupted Current ( $I_u$ )                       | 250 A   |
| Release   | Ekip I  |
| Release Type  | EL  |
| Short-Circuit   | H   |

Performance Level

|                          |                        |
|--------------------------|------------------------|
| Standards                | IEC                    |
| Sub-type                 | XT4                    |
| Terminal Connection Type | Fixed Circuit-Breakers |
| Version                  | F                      |

**Certificates and Declarations (Document Number)**

|                                   |                                    |
|-----------------------------------|------------------------------------|
| Data Sheet, Technical Information | 1SDC210100D0205<br>1SDC210099D0205 |
| Declaration of Conformity - CE    | 9AKK106713A5529                    |
| Environmental Information         | 1SDL000190R0001                    |
| GL Certificate                    | 1SDL000163R0095                    |
| Instructions and Manuals          | 1SDH000722R0001                    |
| LR Certificate                    | 1SDL000163R0100                    |

**Classifications**

|                            |  |
|----------------------------|--|
| ETIM 4                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 5                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 6                     | EC000228 - Power circuit-breaker for trafo/generator/installation prot.      |
| ETIM 7                     | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q  |
| UNSPSC                     | 39120000   |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm)                   |

**Categories**

Low Voltage Products and Systems → Circuit Breakers → Moulded Case Circuit Breakers → Tmax XT

