



### Main

Range	TeSys
Product name	TeSys T
Device short name	LTME
Product or component type	Extension module
Device application	Equipment monitoring and control
Range compatibility	TeSys T LTMR motor controller
Supply	Via the controller

### Complementary

[Ui] rated insulation voltage	690 V conforming to UL 508 690 V conforming to CSA C22.2 No 14 690 V conforming to EN/IEC 60947-1
[Uimp] rated impulse withstand voltage	0.8 kV for supply, inputs and outputs conforming to EN/IEC 60947-4-1 6 kV for current or voltage measurement circuit conforming to EN/IEC 60947-4-1
Logic input number	4
Input current	7 mA
Input/Output type	Logic input : < 5 V and <= 15 mA for 5 ms (at state 0) Logic input : < 15 V for 15 ms (at state 1)
Maximum output switching frequency	2 Hz
Operating rate	1800 cyc/h
Contacts type and composition	Without
Metering type	Active power P, P1, P2, P3 Calculated active and reactive energy (+/- W.h, +/- VAR.h) Frequency Power factor Reactive power Q, Q1, Q2, Q3 Voltage U21, U32, U13, V1, V2, V3 Imbalance voltage
Measurement accuracy	5 % active and reactive power 3 % power factor (cos φ > 0.6) 1 % voltage (100...830 V)
Overvoltage category	III
Connection pitch	5.08 mm
Connections - terminals	Connector, 2 solid cable without cable end 0.2...1 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 flexible cable without cable end 0.5...1.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 flexible cable without cable end 0.2...1.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 2 flexible cable with cable end 0.2...1 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 solid cable without cable end 0.2...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 flexible cable without cable end 0.25...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 flexible cable without cable end 0.2...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit Connector, 1 flexible cable with cable end 0.25...2.5 mm <sup>2</sup> /AWG 24...AWG 14 for control circuit
Tightening torque	0.5...0.6 N.m, 3 mm flat screwdriver for control circuit
Pollution degree	3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Electromagnetic compatibility	<ul style="list-style-type: none"> <li>• surges common mode (4 kV) voltage inputs, conforming to EN/IEC 61000-4-5</li> <li>• surges serial mode (2 kV) voltage inputs, conforming to EN/IEC 61000-4-5</li> <li>• surges common mode (2 kV) communication, conforming to EN/IEC 61000-4-5</li> <li>• surges serial mode (1 kV) control circuit, conforming to EN/IEC 61000-4-5</li> <li>• surges common mode (1 kV) control circuit, conforming to EN/IEC 61000-4-5</li> <li>• conducted RF disturbances (10 V), conforming to EN/IEC 61000-4-6</li> <li>• fast transients immunity test on supply and relay outputs level 4 (4 kV), conforming to EN/IEC 61000-4-4</li> <li>• fast transients immunity test other circuits level 3 (2 kV), conforming to EN/IEC 61000-4-4</li> <li>• electrostatic discharge 3 (8 kV air, 6 kV contact), conforming to EN/IEC 61000-4-2</li> </ul>
Width	45 mm
Height	61 mm
Depth	120.7 mm
Product weight	0.21 kg
Compatibility code	LTME

## Environment

Standards	EN 60947-4-1 IACS E10 IEC 60947-4-1 UL 508 CSA C22.2 No 14
Product certifications	ABS ATEX BV CCC CSA C-Tick DNV GL KERI LROS (Lloyds register of shipping) NOM RINA RMRoS UL EAC
Protective treatment	TH conforming to EN/IEC 60068 48 h conforming to EN/IEC 60070-2-11 12 x 24 hour cycles conforming to EN/IEC 60068-2-30
Fire resistance	960 °C conforming to UL 94 650 °C conforming to EN/IEC 60695-2-12
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-40...80 °C
Operating altitude	<= 2000 m without derating
Mechanical robustness	<ul style="list-style-type: none"> <li>• vibrations plate mounted (4 Gn, 5...300 Hz) conforming to EN/IEC 60068-2-6</li> <li>• vibrations mounted on symmetrical rail (1 Gn, 5...300 Hz) conforming to EN/IEC 60068-2-6</li> <li>• shocks half sine wave acceleration (15 Gn for 11 ms) conforming to EN/IEC 60068-2-27</li> </ul>