

PRODUCT-DETAILS

HSB500-C

SHRINK KON BOX - 6M TRANSP.



General Information

Extended Product Type	HSB500-C
Product ID	7TCA017300R0366
EAN	5414363104445
Catalog Description	SHRINK KON BOX - 6M TRANSP.
Long Description	Thin Wall Heat Shrink Tubing in Dispenser Box - 1/2 Inch Expanded Inside Diameter - 6.0 Meters Transparent

Ordering

EAN	5414363104445
-----	---------------

Dimensions

Product Net Weight	.502 lb 227.664 g
--------------------	----------------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	2.4 in 61 mm
Package Level 1 Height	6.7 in 170 mm

Package Level 1 Depth / Length	6.7 in 170 mm
Package Level 2 Units	60 piece
Package Level 2 Width	15.8 in 401 mm
Package Level 2 Height	22.5 in 572 mm
Package Level 2 Depth / Length	20.9 in 531 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Transparent
Dielectric Test Voltage	280/Mil (11kV/mm) V
Flammability Hazard Rating	Self Extinguishing
Number of Batteries	0
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	Plastic conduit
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	2:1
Shrink Temperature	230 °F 110 °C
Thickness	Thin
UPC	786210564197
Water Absorption	0.03%

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	HSB500-C
Instructions and Manuals	HSB500-C

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

