

PRODUCT-DETAILS

3125RS6W

Ind. P&S#3125RS6W



General Information

Extended Product Type	3125RS6W
Product ID	2CMA167252R1000
EAN	7392696672528
Catalog Description	Ind. P&S#3125RS6W
Long Description	Surface socket-outlet, earthing sleeve position 6h, rated current 125A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

Ordering

E-Number (Sweden)	E2416591
E-Number (Finland)	2421231
E-Number (Norway)	1542913
EAN	7392696672528
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	145 mm
Product Net Height	282 mm

Product Net Weight	1.55 kg
Mechanical Drawings	9AKK107991A3850

Container Information

Package Level 1 Width	154 mm
Package Level 1 Depth / Length	182 mm
Package Level 1 Height	378 mm
Package Level 1 Gross Weight	1.7 kg
Package Level 1 EAN	7392696672528
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	96.5 kg
Package Level 2 EAN	7392696072564
Package Level 2 Units	pallet (lift) 45 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	16 ... 70 mm ²
Cable Entry Position	Cable entry Ø 50mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#3125RS6W

Mounting Holes	188x102
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I_n)	125 A
Rated Voltage (U_r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	3 ... 1 AWG
Tightening Torque	WireClamp5.6 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Tough & Safe → Surface Socket Outlets

