

PRODUCT-DETAILS

BPC32

Building site connection unit, with MCB/RCD,
32A, IP44



General Information

Extended Product Type	BPC32
Product ID	2CMA170268R1000
EAN	7392696702683
Catalog Description	Building site connection unit, with MCB/RCD, 32A, IP44
Long Description	Building Site Connection Unit, BPC32, 32 A, Inlet 32A,400V. Outlet 1x32A.400V, for looping 1x16A, 400V with MCB 4x16A Schuko 230V with MCB 2+2 16A RCD 40A 30mA, 6 hour, Building site connection unit, with MCB/RCD, 32A, IP44,

Ordering

E-Number (Sweden)	E2466372
E-Number (Finland)	2466372
E-Number (Norway)	2466372
EAN	7392696702683
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	400 mm
-------------------	--------

Product Net Height	475 mm
Product Net Weight	3.4 kg

Container Information

Package Level 1 Width	120 mm
Package Level 1 Depth / Length	400 mm
Package Level 1 Height	475 mm
Package Level 1 Gross Weight	3.4 kg
Package Level 1 EAN	7392696702683
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	Inlet 32A,400V. Outlet 1x32A.400V, for looping 1x16A, 400V with MCB 4x16A Schuko 230V with MCB 2+2 16A RCD 40A 30mA
Ambient Temperature	-25 ... 40 °C
Cable Length	0 m
Color	Red
Connection Type	CEE 32 A Connector
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Building site connection unit
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#BPC32
Mounting Type	Portable
Number of Poles	5
Number of RCDs 30mA	2
Number of RCDs	2
Number of Schuko Outlets	4
Order Multiple	1 piece
Product Main Type	BPC
Product Name	Building Site Connection Unit

Rated Current (I _n)	32 A
Rated Residual Current	30 mA
Rated Voltage (U _r)	400 V
Standards	IEC 60309-1, -2 IEC 61439-4
Sub-Function	Inlet 32A,400V. Outlet 1x32A.400V, for looping 1x16A, 400V with MCB 4x16A Schuko 230V with MCB 2+2 16A RCD 40A 30mA
Suitable For	Building site
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440501
UNSPSC	39121406

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Appliances

