

PRODUCT-DETAILS

363MM1

Switched interlocked socket-outlet, 1h, 63A, IP44, 3P+E



General Information

Extended Product Type	363MM1
Product ID	2CMA168040R1000
EAN	7392696680400
Catalog Description	Switched interlocked socket-outlet, 1h, 63A, IP44, 3P+E
Long Description	Switched Interlocked Socket Outlet, metal, earthing sleeve position 1h, rated current 63A, IP44 splashproof, 3-poles+earth

Ordering

E-Number (Sweden)	2417111
E-Number (Finland)	2417111
E-Number (Norway)	2417111
EAN	7392696680400
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	165 mm
Product Net Height	177 mm

Product Net Weight	2.5 kg
--------------------	--------

Container Information

Package Level 1 Width	170 mm
Package Level 1 Depth / Length	300 mm
Package Level 1 Height	185 mm
Package Level 1 Gross Weight	2.67 kg
Package Level 1 EAN	7392696680400
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	206.9 kg
Package Level 2 EAN	7392696076302
Package Level 2 Units	pallet (lift) 70 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Cable Entry Position	Top and bottom
Cable Outlets Per Side	4xM40
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	AC Hz
Function	Switched Interlocked Socket Outlet, metal
Housing Material	Aluminium
Invoice Description	Ind. P&S#363MM1
Mounting Holes	1819944

Mounting Type	Vertical
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CMM
Product Name	Industrial Switched Interlocked Socket Outlet
Protection Type	Switched Interlocked
Rated Current (I_n)	63 A
Rated Voltage (U_r)	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Sub-Function	Cable entry, 4xM40
Suitable For	Switched Interlocked Socket Outlets in Metal
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000042M0001
Installation Manual	2CMC000042M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets in Metal

