

## PRODUCT-DETAILS

# OT315E04C

## OT315E04C CHANGE-OVER SWITCH



### General Information

|                       |                                               |
|-----------------------|-----------------------------------------------|
| Extended Product Type | OT315E04C                                     |
| Product ID            | 1SCA022775R1030                               |
| EAN                   | 6417019252285                                 |
| Catalog Description   | OT315E04C CHANGE-OVER SWITCH                  |
| Long Description      | Handle and shaft has to be ordered separately |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC303003C0201 |
| Instructions and Manuals          | 1SCC303008M0203 |

### Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 265 mm |
| Product Net Height | 185 mm |

|                            |                     |
|----------------------------|---------------------|
| Product Net Depth / Length | 203 mm              |
| Product Net Weight         | 7.08 kg<br>15.61 lb |

## Technical

|                                                    |                                                            |
|----------------------------------------------------|------------------------------------------------------------|
| Rated Operational Current AC-21A ( $I_e$ )         | (380 ... 415 V) 315 A<br>(500 V) 315 A<br>(690 V) 315 A    |
| Rated Operational Current AC-22A ( $I_e$ )         | (380 ... 415 V) 315 A<br>(500 V) 315 A<br>(690 V) 315 A    |
| Rated Operational Current AC-23A ( $I_e$ )         | (380 ... 415 V) 315 A<br>(500 V) 315 A<br>(690 V) 315 A    |
| Rated Operational Current AC-31B ( $I_e$ )         | (380 ... 415 V) 315 A                                      |
| Rated Operational Current AC-33B ( $I_e$ )         | (380 ... 415 V) 315 A                                      |
| Rated Operational Power AC-23A ( $P_e$ )           | (380 ... 415 V) 160 kW<br>(500 V) 220 kW<br>(690 V) 315 kW |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | $q = 40\text{ °C}$ 315 A                                   |
| Conventional Thermal Current ( $I_{the}$ )         | Fully Enclosed 315 A                                       |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 12 kV                                                      |
| Rated Insulation Voltage ( $U_i$ )                 | 1000 V                                                     |
| Rated Operational Voltage                          | 1000 V                                                     |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | for 1 s 15 kiloampere rms                                  |
| Power Loss                                         | 6.5 W                                                      |
| Pollution Degree                                   | 3                                                          |
| Handle Color                                       | Black                                                      |
| Handle Type                                        | Handle and shaft not included                              |
| Fourth Pole Position                               | Right Side                                                 |
| Fourth Pole Type                                   | Switched - Simultaneous Function                           |
| Switches Operating Mechanism                       | Mechanism at the End of the Switch<br>04 (Left Side)       |
| Distance Between Phases                            | Standard                                                   |
| Position of Line Terminals                         | Top In - Bottom Out, Bottom In - Top Out                   |
| Operating Mode                                     | Front operated                                             |
| Mounting Type                                      | Base mounting                                              |
| Number of Poles                                    | 4                                                          |
| Degree of Protection                               | Front IP20                                                 |
| Transition Type                                    | Open                                                       |

## Environmental

|                           |                 |
|---------------------------|-----------------|
| Environmental Information | 1SCC303050D0201 |
|---------------------------|-----------------|

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of<br>Conformity - CE | 1SCC303004D0202 |
| Environmental<br>Information      | 1SCC303050D0201 |
| Instructions and<br>Manuals       | 1SCC303008M0203 |

**Container Information**

|                                   |                    |
|-----------------------------------|--------------------|
| Package Level 1 Units             | 1 piece            |
| Package Level 1 Width             | 240 mm             |
| Package Level 1 Depth /<br>Length | 325 mm             |
| Package Level 1 Height            | 218 mm             |
| Package Level 1 Gross<br>Weight   | 7.53 kg<br>16.6 lb |
| Package Level 1 EAN               | 6417019252285      |

**Classifications**

|                               |                                                            |
|-------------------------------|------------------------------------------------------------|
| Object Classification<br>Code | Q                                                          |
| ETIM 5                        | EC000216 - Switch disconnecter                             |
| ETIM 6                        | EC000216 - Switch disconnecter                             |
| ETIM 7                        | EC000216 - Switch disconnecter                             |
| WEEE Category                 | 5. Small Equipment (No External Dimension More Than 50 cm) |

**Categories**

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual Change-over Switches

