

PRODUCT-DETAILS

232RS6B

Surface socket outlets, 2P+E, 32 A, 200 ... 250 V



General Information

Extended Product Type	232RS6B
Product ID	2CMA101024R1000
EAN	7392696010245
Catalog Description	Surface socket outlets, 2P+E, 32 A, 200 ... 250 V
Long Description	Surface socket outlets, 2P+E, IP44, 32 A, 200 ... 250 V

Ordering

E-Number (Finland)	2420320
E-Number (Norway)	1543467
EAN	7392696010245
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	85 mm
Product Net Height	118 mm
Product Net Weight	0.331 kg
Mechanical Drawings	9AKK107680A0704

Container Information

Package Level 1 Width	175 mm
Package Level 1 Depth / Length	428 mm
Package Level 1 Height	188 mm
Package Level 1 Gross Weight	3.31 kg
Package Level 1 EAN	7392696014250
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1344 kg
Package Level 2 EAN	7392696065214
Package Level 2 Units	pallet (lift) 400 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm²
Cable Diameter	22 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry.
Color	Blue
Connection Type	Screw
Cover Color	Black
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)

Invoice Description	IND. P&S#232RS6B
Mounting Holes	111x72
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

