

PRODUCT-DETAILS

OTM315E3YM230C

OTM315E3YM230C MOTORIZED BYPASS SWITCH



General Information

Extended Product Type	OTM315E3YM230C
Product ID	1SCA141440R1001
EAN	6417019690315
Catalog Description	OTM315E3YM230C MOTORIZED BYPASS SWITCH
Long Description	OTM315E3YM230C MOTORIZED BYPASS SWITCH, Direct mounted handle, Open transition

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

Dimensions

Product Net Width	342 mm
-------------------	--------

Product Net Height	185 mm
Product Net Depth / Length	285 mm
Product Net Weight	12 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 160 kW (500 V) 220 kW (690 V) 315 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 315 A
Motor Operational Voltage	220 ... 240 V AC
Handle Type	Direct mounted handle
Switches Operating Mechanism	Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	3
Transition Type	Open

Certificates and Declarations (Document Number)

Instructions and Manuals	1SCC301080M0003
--------------------------	-----------------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Gross Weight	25 kg
Package Level 1 EAN	6417019690315

Classifications

WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
---------------	--

Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized bypass switches

