

PRODUCT-DETAILS

216QRM6

Ind. P&S#216QRM6



General Information

Extended Product Type	216QRM6
Product ID	2CMA102288R1000
EAN	7392696022880
Catalog Description	Ind. P&S#216QRM6
Long Description	Panel mounted socket outlets, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue, minimized straight flange, Screwless terminals

Ordering

E-Number (Sweden)	E2404975
E-Number (Finland)	2420274
EAN	7392696022880
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	70 mm
Product Net Height	86 mm

Product Net Weight	0.107 kg
--------------------	----------

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.253 kg
Package Level 1 EAN	7392696037648
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Color	Blue
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216QRM6
Mounting Holes	56x56
Number of Poles	3
Order Multiple	10 piece
Product Main Type	QRM
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I _N)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	200 ... 250 V

Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 5015 - Sky Blue

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

