

PRODUCT-DETAILS

PSR105-600-70

PSR105-600-70 Softstarter



General Information

Global Commercial Alias	PSR105-600-70
Extended Product Type	PSR105-600-70
Product ID	1SFA896115R7000
ABB Type Designation	PSR105-600-70
EAN	7320500362655
Catalog Description	PSR105-600-70 Softstarter
Long Description	Softstarter PSR105-600-70 for max 600V main voltage and 100-240V 50/60Hz control supply voltage

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85044090

Popular Downloads

Data Sheet, Technical Information	1SFC132005C0201
Instructions and Manuals	1SFC132033M0001

Dimensions

Product Net Width	180 mm
Product Net Height	220 mm
Product Net Depth / Length	70 mm
Product Net Weight	2.1 kg

Technical

Rated Operational Voltage	208 ... 600 V AC
Rated Control Supply Voltage (U _s)	100 ... 240 V AC
Rated Control Circuit Voltage (U _c)	50 Hz / 60 Hz 100 ... 240 V AC
Rated Frequency (f)	50/60 Hz Main Circuit 50/60 Hz
Rated Operational Power - In-Line Connection (P _e)	(230 V) 30 kW (400 V) 55 kW (500 V) 55 kW
Rated Operational Current - In-Line Connection (I _e)	105 A
Service Factor Percentage	100 %
Overload Protection	Recommended MS495 80 ... 100
Integrated Electronic Overload	No
Adjustable Rated Motor Current I _e	No
Starting Capacity at Maximum Rated Current I _e	4xI _e for 6s
Ramp Time	0 ... 20 second [unit of time] 1 ... 10 second [unit of time]
Initial Voltage During Start	40 ... 70 %
Step Down Voltage Special Ramp	100 ... 60 %
Current Limit Function	No
Switch for Inside Delta Connection	No
Run Signal Relay	Yes
By-pass Signal Relay	Yes
Fault Signal Relay	No
Overload Signal Relay	No
Signal indication completed start ramp (LED)	Green
Signal indication ready to start/standby ON (LED)	Green
Signal indication running R (LED)	Green
Signal indication ramping up/down (LED)	Green
Number of Starts Per Hour at 3.5*I _e for 7 sec. 50% ON Time 50% OFF Time	10
Communication	FiledBusPlug(Optional)
Degree of Protection	IP10
Terminal Type	Main Circuit: Bars
Connecting Capacity	Rigid 1x 10 ... 95 mm ²

Main Circuit	Rigid 2 x 6 ... 35 mm ²
Connecting Capacity	Rigid 1 x 0.75 ... 2.5 mm ²
Control Circuit	Rigid 2 x 0.75 ... 1.5 mm ²
Connecting Capacity	Rigid 1 x 0.75 ... 2.5 mm ²
Supply Circuit	
Tightening Torque	Control Circuit 0.6 N·m Main Circuit 8 N·m Supply Circuit 0.6 N·m
Product Main Type	PSR105

Environmental

Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Certificates and Declarations (Document Number)

CQC Certificate	CQC2008010304295498
Declaration of Conformity - CCC	2020980304001090
Declaration of Conformity - CE	1SFA1-95
Environmental Information	1SFC132038D0201
Instructions and Manuals	1SFC132033M0001
RoHS Information	1SFC132031D0202

Container Information

Package Level 1 Width	195 mm
Package Level 1 Depth / Length	86 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	2.3 kg
Package Level 1 EAN	7320500362655
Package Level 1 Units	box 1 piece

Classifications

Object Classification Code	Q
ETIM 4	EC002572 - Electronic motor control and protection device
ETIM 5	EC002572 - Electronic motor control and protection device
ETIM 6	EC002572 - Motor management device
UNSPSC	39121521

Categories

Drives → Softstarters → Softstarters → PSR Softstarters → PSR105

Low Voltage Products and Systems → Control Products → Softstarters → Softstarters → PSR Softstarters → PSR105

