

PRODUCT-DETAILS

2/1MF300

2/1MF300 mantle cabinet 30min.



General Information

Extended Product Type	2/1MF300
Product ID	2CPX042422R9999
EAN	4011617424222
Catalog Description	2/1MF300 mantle cabinet 30min.
Long Description	Fire resistance - overstretched housing, series MF, empty cabinet, for the internal use, with Door, class of protection II (double insulated), degree of protection IP41, fire resistance 30 min tested according to , Reduce fire load 30 min in line with , Maintain functionality 30 min in line with , Rated operational voltage 400V AC 50/60 Hz, surface -coated, in RAL 7035, enclosure out of non flammable material, single-leaf door, door out of non flammable material, with Swivel handle with half cylinder, door opening angle 180 degree, door hinge right, cable entry on top via fire stop cable entry, on bottom via fire stop cable entry, dimensions in mm (H x W x D): 979 x 768 x 340, Grid unit 6 GU, Overall height 2, panel width 3, Space units 216, Housing for mouting above located cabinet

Ordering

EAN	4011617424222
Minimum Order Quantity	1 piece
Customs Tariff Number	85381000

Dimensions

Product Net Width	768 mm
Product Net Height	979 mm

Product Net Depth / Length	340 mm
Product Net Weight	124 kg

Container Information

Package Level 1 Units	pack 1 piece
Package Level 1 Width	768.000 mm
Package Level 1 Height	979.000 mm
Package Level 1 Depth / Length	340.000 mm
Package Level 1 Gross Weight	128.96 kg
Package Level 1 EAN	4011617424222
Package Level 2 Units	12 piece
Package Level 2 Width	830 mm
Package Level 2 Height	1710 mm
Package Level 2 Depth / Length	1210 mm

Additional Information

Color	light grey
Configuration Type	Housing for mouting above located cabinet
Cover Plate Type	None
Degree of Protection	IP41
DIN Place Units	216
Enclosure Type	Fire resistance - overstretched housing
Enclosure Type of Height	2
Field Width	3
Interior Depth	240 mm
Meter Boards	0
Mounting Type	Other
Number of Rows	9
Operational Voltage	400 V
Product Main Type	MF
Product Name	2/1MF300 mantle cabinet 30min.
Protection Class	Isolated
Rated Operational Voltage	Maximum 400 V

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CPC000001C0101 2CPC000002C0101
Declaration of Conformity - CE	No declaration needed
Environmental Information	2CPC100001X0201
Instructions and Manuals	2CPC000186C0201

Classifications

ETIM 4	EC000058 - Empty cabinet
ETIM 5	EC000058 - Empty cabinet

ETIM 6	EC000058 - Empty cabinet
ETIM 7	EC000058 - Empty cabinet
Object Classification Code	U
WEEE Category	Product Not in WEEE Scope

Categories

Low Voltage Products and Systems → Enclosures → Sub Distribution Boards → Fire Resistant Enclosures

