

PRODUCT-DETAILS

MCP-S4/250 500V-7h

Ind. P&S#MCP-S4/250 500V-7h



General Information

Extended Product Type	MCP-S4/250 500V-7h
Product ID	2CMA103201R1000
EAN	7392696032018
Catalog Description	Ind. P&S#MCP-S4/250 500V-7h
Long Description	Panel mounted inlet, 3P+E, IP67, 250 A, 200/346 ... 240/415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connectors also suitable for marine applications. Aluminum housing. Designed for high temperature.

Ordering

EAN	7392696032018
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	230 mm
Product Net Height	350 mm

Product Net Weight	8.1 kg
--------------------	--------

Container Information

Package Level 1 Width	277 mm
Package Level 1 Depth / Length	277 mm
Package Level 1 Height	352 mm
Package Level 1 Gross Weight	8.1 kg
Package Level 1 EAN	7392696032018
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+E
Ambient Temperature	-40 ... 100 °C
Cable Diameter	45 ... 66 mm
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Aluminum
Invoice Description	Ind. P&S#MCP-S4/250 500V-7h
Mounting Holes	155x155
Number of Poles	4
Order Multiple	1 piece
Product Main Type	MCP
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	250 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	480...500 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

