


## PRODUCT-DETAILS

# 216MHS9W

Switched interlocked socket-outlet, 9h, 16A, IP67, 2P+E



## General Information

|                       |                                                                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216MHS9W                                                                                                                                                           |
| Product ID            | 2CMA167802R1000                                                                                                                                                    |
| EAN                   | 7392696678025                                                                                                                                                      |
| Catalog Description   | Switched interlocked socket-outlet, 9h, 16A, IP67, 2P+E                                                                                                            |
| Long Description      | Switched Interlocked Socket Outlet, horizontal, earthing sleeve position 9h, rated current 16A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Red |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | 2416895             |
| E-Number (Finland)     | 2416895             |
| E-Number (Norway)      | 2416895             |
| EAN                    | 7392696678025       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 168 mm |
| Product Net Height | 114 mm |

|                    |         |
|--------------------|---------|
| Product Net Weight | 0.62 kg |
|--------------------|---------|

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 135 mm                  |
| Package Level 1 Depth / Length | 140 mm                  |
| Package Level 1 Height         | 200 mm                  |
| Package Level 1 Gross Weight   | 0.7 kg                  |
| Package Level 1 EAN            | 7392696678025           |
| Package Level 1 Units          | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 141.8 kg                |
| Package Level 2 EAN            | 7392696074759           |
| Package Level 2 Units          | pallet (lift) 174 piece |

## Environmental

|             |                                                       |
|-------------|-------------------------------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU                     |
| SCIP        | Czech Republic - b0b30fc0-3a31-41d5-a35f-56a55306b63f |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1515100         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                                                |
|------------------------|------------------------------------------------|
| Additional Information | 2P+E                                           |
| Ambient Temperature    | -25 ... 40 °C                                  |
| Cable Cross-Section    | 1.5 ... 4 mm²                                  |
| Cable Diameter         | 6 ... 13 mm                                    |
| Cable Entry Position   | Top and bottom                                 |
| Cable Outlets Per Side | 1xØ25                                          |
| Color                  | Red                                            |
| Connection Type        | Screw                                          |
| Degree of Protection   | IP67                                           |
| Frequency (f)          | 50 Hz<br>60 Hz                                 |
| Function               | Switched interlocked socket outlet, horizontal |

|                            |                                                 |
|----------------------------|-------------------------------------------------|
| Housing Material           | Thermoplastic (PBT)                             |
| Invoice Description        | Ind. P&S#216MHS9W                               |
| Mounting Holes             | 146x91                                          |
| Mounting Type              | Horizontal                                      |
| Number of Poles            | 3                                               |
| Order Multiple             | 1 piece                                         |
| Product Main Type          | CMHS                                            |
| Product Name               | Industrial Switched Interlocked Socket Outlet   |
| Protection Type            | Switched Interlocked                            |
| Rated Current ( $I_n$ )    | 16 A                                            |
| Rated Voltage ( $U_r$ )    | 380 ... 415 V                                   |
| Recommended Screw Driver   | PH2                                             |
| Standards                  | IEC 60309-1, -2, -4                             |
| Suitable For               | Switched Interlocked Socket Outlets, Horizontal |
| Suitable for Product Class | IEC Industrial Plugs and Sockets                |
| Instructions and Manuals   | 2CMC000032M0001                                 |
| Installation Manual        | 2CMC000032M0001                                 |
| RAL Number                 | RAL 7001 - Silver Grey                          |

## Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

