

PRODUCT-DETAILS

EXLB0920

FLEXIBLE CONDUIT 63MM OIL RESISTANT



General Information

Extended Product Type	EXLB0920
Product ID	7TCA297120R0083
EAN	5011949001732
Catalog Description	FLEXIBLE CONDUIT 63MM OIL RESISTANT
Long Description	Liquid Tight Metallic Conduit, Oil and Dilute Acid Resistant, Conduit Size 63mm, Minimum Bore 51.6mm, Reel Length 20 Meters, Galvanised Steel Core with Flame Retardant PVC Covering, Black

Additional Information

Application	Connection for Conduit Systems when Oil and Acid Resistance is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949001732
UPC	786210263311
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	20 m
----------------------------	------

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Flame Retardant PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	1 in 25 mm
Package Level 1 Depth / Length	1 in 25 mm
Package Level 1 Width	1 in 25 mm

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	EXLB0920
Instructions and Manuals	EXLB0920
Declaration of Conformity - CE	9AKK107492A9617

Classifications	
UNSPSC	39131706

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

