

PRODUCT-DETAILS

OS50GF11P

OS50GF11P SWITCH FUSE



General Information

Extended Product Type	OS50GF11P
Product ID	1SCA116870R1001
EAN	6417019488134
Catalog Description	OS50GF11P SWITCH FUSE
Long Description	Switch Fuses,Front Operated,2-pole,11 (Between the Poles),NFC,14x51,Handle and shaft included,

Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

Popular Downloads

Data Sheet, Technical Information	1SCC311136D2703
Instructions and Manuals	1SCC311036M0212

Dimensions

Product Net Width	112 mm
Product Net Height	112 mm

Product Net Depth / Length	109 mm
Product Net Weight	1.11 kg 2.45 lb

Technical

Rated Operational Current AC-21A (I_e)	(500 V) 50 A (690 V) 50 A
Rated Operational Current AC-22A (I_e)	(500 V) 50 A (690 V) 50 A
Rated Operational Current AC-23A (I_e)	(500 V) 50 A (690 V) 50 A
Rated Operational Power AC-23A (P_e)	(220 ... 240 V) 11 kW (400 V) 22 kW (415 V) 22 kW (500 V) 30 kW (690 V) 37 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 50 A
Conventional Thermal Current (I_{the})	Fully Enclosed 50 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current (I_{cw})	for 1 s 2.5 kiloampere rms
Rated Conditional Short-Circuit Current (I_{nc})	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 7.5 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Switches Operating Mechanism	11 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	14x51
Fuse System	NFC
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	2
Cable Cross-Section	2.5 ... 25 mm ²
Terminal Type	Screw Terminals
Tightening Torque	3 N·m 4 N·m
Fuse Type	NFC

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificates and Declarations (Document Number)

CCC Certificate	CCC OS32-63G_2016.pdf
Declaration of	1SCC311136D2703

Conformity - CE

DNV GL Certificate	1SCC311125D0203
--------------------	-----------------

EAC Certificate

OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_pdf	EAC
---	-----

Instructions and Manuals

1SCC311036M0212

RoHS Information

1SCC311136D2703

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	146 mm 5.75 in
Package Level 1 Depth / Length	192 mm 7.56 in
Package Level 1 Height	137 mm 5.39 in
Package Level 1 Gross Weight	1.25 kg 2.76 lb
Package Level 1 EAN	6417019488134

Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switches → Switch Fuses

