

## PRODUCT-DETAILS

# 432QR9

## Ind. P&S#432QR9



### General Information

|                       |                                                                                                                                                                                 |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 432QR9                                                                                                                                                                          |
| Product ID            | 2CMA102958R1000                                                                                                                                                                 |
| EAN                   | 7392696029582                                                                                                                                                                   |
| Catalog Description   | Ind. P&S#432QR9                                                                                                                                                                 |
| Long Description      | Panel mounted socket outlets, earthing sleeve position 9h, 3P+N+E, IP44 splashproof, 32 A, 120/208 ... 144/250 V, unified straight flange, color code Blue, Screwless terminals |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 7392696029582 |
| Country of Origin      | Turkey (TR)   |
| Minimum Order Quantity | 10 piece      |

### Dimensions

|                    |           |
|--------------------|-----------|
| Product Net Width  | 75 mm     |
| Product Net Height | 105 mm    |
| Product Net Weight | 0.1762 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 150 mm        |
| Package Level 1 Depth / Length | 280 mm        |
| Package Level 1 Height         | 225 mm        |
| Package Level 1 Gross Weight   | 1.945 kg      |
| Package Level 1 EAN            | 7392696042970 |
| Package Level 1 Units          | box 10 piece  |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000072M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                            |                                  |
|----------------------------|----------------------------------|
| Additional Information     | 3P+N+E                           |
| Ambient Temperature        | -25 ... 40 °C                    |
| Cable Cross-Section        | 2.5 ... 10 mm²                   |
| Color                      | Blue                             |
| Connection Type            | Screwless                        |
| Degree of Protection       | IP44                             |
| Frequency (f)              | 50 Hz<br>60 Hz                   |
| Function                   | Outlet                           |
| Housing Material           | Plastic (PA)                     |
| Invoice Description        | Ind. P&S#432QR9                  |
| Mounting Holes             | 60x60                            |
| Number of Poles            | 5                                |
| Order Multiple             | 10 piece                         |
| Product Main Type          | QR                               |
| Product Name               | Panel mounted socket             |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 32 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 120/208 ... 144/250 V            |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |

RAL Number

RAL 5015 - Sky Blue

Classifications

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

