
PRODUCT-DETAILS

RLV216

Industrial Socket Outlet Panel Mounting, 2P, 16 A, 20 ... 25 AC V



General Information

Extended Product Type	RLV216
Product ID	2CMA100973R1000
EAN	7392696009737
Catalog Description	Industrial Socket Outlet Panel Mounting, 2P, 16 A, 20 ... 25 AC V
Long Description	Industrial Socket Outlet Panel Mounting Extra low voltage 16 A, RLV 216, splashproof

Ordering

E-Number (Sweden)	E2417749
EAN	7392696009737
Country of Origin	Austria (AT)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	55 mm
Product Net Height	79 mm
Product Net Weight	0.099 kg

Container Information

Package Level 1 Width	62 mm
Package Level 1 Depth / Length	62 mm
Package Level 1 Height	81 mm
Package Level 1 Gross Weight	0.99 kg
Package Level 1 EAN	7392696009973
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 10 mm ²
Cable Diameter	8 ... 24 mm
Color	Purple
Connection Type	Screw
Degree of Protection	IP44
Function	Extra low voltage panel mounted socket
Housing Material	Plastic
Invoice Description	Ind. P_S#RLV216
Mounting Holes	44x44
Number of Poles	2
Order Multiple	10 piece
Product Main Type	RLV
Product Name	Extra low voltage panel mounted socket
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	20 ... 25 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets for Extra Low Voltage

