

PRODUCT-DETAILS

# OT250E12YP

## OT250E12YP BY-PASS SWITCH



### General Information

Extended Product Type	OT250E12YP
Product ID	1SCA123565R1001
EAN	6417019543499
Catalog Description	OT250E12YP BY-PASS SWITCH
Long Description	Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC301080M0003

## Dimensions

Product Net Width	194 mm
Product Net Height	150 mm
Product Net Depth / Length	236 mm
Product Net Weight	5.23 kg 11.53 lb

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 250 A (500 V) 250 A (690 V) 250 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 140 kW (500 V) 170 kW (690 V) 250 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 250 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 250 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 8 kiloampere rms
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included
Switches Operating Mechanism	Mechanism Between the Poles 12 (Between the Poles)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Degree of Protection	Front IP20
Transition Type	Open

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC301194D0202
Instructions and Manuals	1SCC301080M0003

## Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	175 mm
Package Level 1 Depth / Length	360 mm
Package Level 1 Height	350 mm
Package Level 1 Gross Weight	5.74 kg 12.65 lb
Package Level 1 EAN	6417019543499

---

### Classifications

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

---

### Categories

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual bypass switches

