

PRODUCT-DETAILS

JSTD25H

JSTD25H Twohand station, 8-pole M12 Male



General Information

Extended Product Type	JSTD25H
Product ID	2TLA020007R6300
EAN	7350024460346
Catalog Description	JSTD25H Twohand station, 8-pole M12 Male
Long Description	Two-hand device with JSTD1-B Safeballs. Buttons are side mounted on a 44x88 extruded aluminum profile designed for two-hand applications. Pre-wired to a M12 8-pin connector with protective flanges of the safeballs. Highest level of safety can be achieved when used in conjunction with a JSBR4 safety relay or Pluto Safety PLC.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365011

Popular Downloads

Data Sheet, Technical Information	2TLC010001C0202
Instructions and Manuals	2TLC172185M0201
Marketing Video	2TLC010018N0201

Dimensions

Product Net Depth / Length	90.5 mm
Product Net Height	130 mm
Product Net Width	370 mm
Product Net Weight	1.167 kg

Technical

Performance Level (PL)	Up to e
------------------------	---------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2TLC172023D0201
Instructions and Manuals	2TLC172185M0201
SEMKO Certificate	2TLC172034D0201

Classifications

Object Classification Code	B
ETIM 4	EC001260 - Two-hand control device
ETIM 5	EC001260 - Two-hand control device
ETIM 6	EC001260 - Two-hand control device
ETIM 7	EC001260 - Two-hand control device
eClass	V11.0 : 27371219
UNSPSC	32151802

Categories

Low Voltage Products and Systems → Control Products → Safety Products → Safety Control Devices

