

PRODUCT-DETAILS

BZL1250A-1P-M12

BZL1250A-1P-M12 Switch disconnecter



General Information

Extended Product Type	BZL1250A-1P-M12
Product ID	1SEP620083R1000
EAN	7025840093442
Catalog Description	BZL1250A-1P-M12 Switch disconnecter
Long Description	BZL1250A-1P-M12 Switch disconnecter

Ordering

Customs Tariff Number	85389099
Country of Origin	Bulgaria (BG)

Popular Downloads

Data Sheet, Technical Information	1SEC312023D0201
-----------------------------------	-----------------

Dimensions

Product Frame Size	Low
Product Net Width	99 mm
Product Net Height	775 mm
Product Net Depth / Length	248 mm

Product Net Weight	11.2 kg
--------------------	---------

Technical

Rated Operational Current AC-21B (I _e)	(690 V) 1250 A (500 V) 1250 A (400 V) 1250 A
Rated Operational Current AC-22B (I _e)	(400 V) 1600 A
Rated Operational Current AC-23B (I _e)	(400V) 1600 A
Rated Impulse Withstand Voltage (U _{imp})	Main Circuit 8 kV
Rated Insulation Voltage (U _i)	1000 V
Rated Operational Voltage	690 V AC
Rated Short-Circuit Making Capacity (I _{cm})	20 kA
Rated Short-time Withstand Current (I _{cw})	for 1 s 15 kiloampere rms
Handle Type	1P
Distance Between Phases	185 mm
Fuse Size	Solid link
Standards	IEC60947-3
Number of Poles	3
Degree of Protection	Front IP30
Terminal Type	Bolt
Device Type Manager (DTM)	Switch disconnector
Fuse Type	Solid link
Electronic Fuse Monitoring	No

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SEP500046P0001
RoHS Information	9AKK107991A6284

Container Information

Package Level 1 Units	shrink-wrap 1 piece
Package Level 1 EAN	7025840093442

Classifications

ETIM 4	EC000216 - Switch disconnector
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector

WEEE Category 4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Fusegear → Fuse Switch Disconnectors → Inline II

