

PRODUCT-DETAILS

CR-P024TRI1

CR-P024TRI1 Interface Opto Input= 24 V DC,
Output= 3 A/240 V AC



General Information

Extended Product Type	CR-P024TRI1
Product ID	1SVR405610R4070
EAN	4013614509414
Catalog Description	CR-P024TRI1 Interface Opto Input= 24 V DC, Output= 3 A/240 V AC
Long Description	CR-P024TRI1 Interface Opto Input= 24 V DC, Output= 3 A/240 V AC Triac

Ordering

Minimum Order Quantity	10 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC110004C0210_05
Instructions and Manuals	1SVC405600M9000

Dimensions

Product Net Width	12.7 mm
Product Net Height	15.7 mm
Product Net Depth /	29 mm

Length

Product Net Weight	0.011 kg
--------------------	----------

Technical

Function	Pluggable pcb optocoupler CR-P
Output	TRIAC
Output Signal	275VAC / 3A
Rated Control Supply Voltage (U _s)	10 ... 32 V DC

Environmental

Ambient Air Temperature	Operation -20 ... +50 °C Storage -20 ... +70 °C
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

cUR Certificate	cUR_E244330
Declaration of Conformity - CE	1SVD982057-0000
Instructions and Manuals	1SVC405600M9000
RoHS Information	1SVD981001-4400
UR Certificate	UR_E244330

Container Information

Package Level 1 Units	box 10 piece
Package Level 1 Width	316.7 mm
Package Level 1 Height	23.4 mm
Package Level 1 Depth / Length	15.3 mm
Package Level 1 Gross Weight	0.13 kg
Package Level 1 EAN	4013614509377

Classifications

ETIM 5	EC001504 - Optocoupler
ETIM 6	EC001504 - Optocoupler
ETIM 7	EC001504 - Optocoupler
eClass	V11.0 : 27371604
UNSPSC	32111705

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Interface Relays and Optocouplers

