


PRODUCT-DETAILS

MO132-0.25

MO132-0.25 Manual Motor Starter Magnetic Only



Общая информация

Тип расширенного изделия	MO132-0.25
Идентификационный номер изделия	1SAM360000R1002
Европейский товарный код (EAN)	4013614400179
Описание в каталоге	MO132-0.25 Manual Motor Starter Magnetic Only

Длинное описание

The MO132-0.25 manual motor starter magnetic only is a compact 45 mm width device with a rated operational current of $I_e = 0.25$ A. This device is used to manually switch on and off loads/motors and to protect them reliably and without the need for a fuse from short-circuits. The manual motor starter offers a rated service short-circuit breaking capacity $I_{cs} = 50$ kA at 400 V AC. A combination together with overload relays or motor controllers allows the protection of motors. Further features are the built-in disconnect function, trip-free mechanism and a rotary handle with a clear switch position indication. The manual motor starter magnetic only is suitable for three- and single-phase applications. The handle is lockable to protect against unauthorized changes. Auxiliary contacts, signalling contacts, undervoltage releases, shunt trips, 3-phase bus bars, power in-feed blocks are available as accessory.

Ordering

Минимальный объем заказа	1 штука
Номер таможенного тарифа	85362010

Popular Downloads

Технические данные	2CDC131035D0202
Инструкции и руководства	2CDC131034M6801
Инструкции и руководства (часть 2)	2CDC131060M0202
Time-Current Characteristic Curve	1SAM300515F0001

Dimensions

Чистая ширина изделия	45 mm
Чистая высота изделия	90 mm
Чистая толщина изделия	86.75 mm
Чистый вес изделия	0.215 kg

Technical

Номинальная рабочая отключающая способность при коротком замыкании (I_{cs})	(230 В AC) 100 kA (400 В AC) 100 kA (440 В AC) 100 kA (500 В AC) 100 kA (690 В AC) 100 kA
Номинальная предельная отключающая способность при коротком замыкании (I_{cu})	(230 В AC) 100 kA (400 В AC) 100 kA (440 В AC) 100 kA (500 В AC) 100 kA (690 В AC) 100 kA
Уставка номинального мгновенного тока короткого замыкания (I_i)	3.1 A
Диапазон настройки	None
Номинальная рабочая мощность, АС-3 (P_e)	(400 V) Three Phase 0.06 kW
Номинальная рабочая мощность, АС-3е (P_e)	(400 V) Three Phase 0.06 kW
Номинальное рабочее напряжение	Главная цепь 690 V AC
Номинальный рабочий ток (I_e)	0.25 A
Номинальный рабочий ток, АС-3 (I_e)	0.25 A
Номинальный рабочий ток, АС-3е (I_e)	0.25 A
Номинальная частота (f)	Главная цепь 50 Hz Главная цепь 60 Hz
Номинальное выдерживаемое импульсное напряжение (U_{imp})	Главная цепь 6 kV
Номинальное напряжение изоляции (U_i)	690 V

Потери мощности

at Rated Operating Conditions per Pole 1.7 W

Количество полюсов	3
Условный тепловой ток на открытом воздухе (I_{th})	Main Circuit 0.25 A
Степень защиты	Housing IP20 Main Circuit Terminals IP10
Степень загрязнения	степень загрязнения 3
Коммутационная износостойкость	50000 цикл
Механическая износостойкость	100000 цикл
Тип клемм	Клеммы с винтовым зажимом
Сечение подключаемого кабеля-главная цепь	Гибкий с зажимом 1/2x 0.75 ... 2.5 mm ² Гибкий с изолированным зажимом 1/2x 0.75 ... 2.5 mm ² Гибкий 1/2x 0.75 ... 2.5 mm ² Жесткий 1/2x 1 ... 4 mm ²
Крутящие моменты затяжки	Главная цепь 0.8 ... 1.2 N·m
Длина зачистки провода	Главная цепь 9 mm
Рекомендуемый инструмент (отвертка)	Pozidriv 2
Монтажное положение	Position 1 to 6
Монтаж на DIN-рейке	Монтажная рейка 35 x 15 mm Монтажная рейка 35 x 7,5 mm
Minimum Mounting Distance	Electrical Conductive Board, Horizontal - Up to 400 V 0 mm Electrical Conductive Board, Horizontal - Up to 690 V 1.5 mm Electrical Conductive Board, Vertical 75 mm Other Device Same Type, Horizontal 0 mm Other Device Same Type, Vertical 150 mm
Тип исполнительного элемента (рабочая головка)	Rotary Handle
Contact Position Indication	ON / OFF / TRIP
Стандарты	IEC/EN 60947-1 IEC/EN 60947-2 IEC/EN 60947-4-1 UL 60947-1 UL 60947-4-1
Замечания	For overload protection of the motors, an appropriate thermal or electronic overload relays must be used

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	Any UL Listed Fuses or Circuit-Breakers, Group Installations (480 V AC) 65 kA Any UL Listed Fuses or Circuit-Breakers, Group Installations (600 V AC) 47 kA Any UL Listed Fuses or Circuit-Breakers, Motor Disconnect (480 V AC) 65 kA Any UL Listed Fuses or Circuit-Breakers, Motor Disconnect (600 V AC) 47 kA Any UL Listed Fuses or Circuit-Breakers, Tap Conductor Protection in Group Installations (480Y / 277 V AC) 65 kA Any UL Listed Fuses or Circuit-Breakers, Tap Conductor Protection in Group Installations (600Y / 347 V AC) 47 kA
Maximum Operating Voltage UL/CSA	Главная цепь 600 V AC
Номинальный ток UL	0.25 A
Full Load Amps Motor Use	(200 V AC) Three Phase 0.25 A (208 V AC) Three Phase 0.25 A (220 ... 240 V AC) Three Phase 0.25 A (440 ... 480 V AC) Three Phase 0.25 A

	(550 ... 600 V AC) Three Phase 0.25 A
Locked Rotor Amps	(200 V AC) Three Phase 1.5 A (208 V AC) Three Phase 1.5 A (220 ... 240 V AC) Three Phase 1.5 A (440 ... 480 V AC) Three Phase 1.5 A (550 ... 600 V AC) Three Phase 1.5 A
General Use Rating UL/CSA	(600 V AC) 0.25 A
Connecting Capacity Main Circuit UL/CSA	Гибкий 1/2x 16-12 AWG Многожильный 1/2x 16-12 AWG
Tightening Torque UL/CSA	Главная цепь 10 in-lb

Environmental

Температура окружающей среды	Снаружи корпуса 0 ... +40 °C Работа с компенсацией -25 ... +60 °C Хранение -50 ... +80 °C
Компенсация температуры окружающей среды	Нет
Максимально допустимая рабочая высота	2000 m
Ударопрочность согласно МЭК 60068-2- 27	Импульс 11 мс 25g
Вибропрочность согласно МЭК 60068-2-6	5g / 3 ... 150 Hz
Правила ограничения содержания вредных веществ. RoHS статус	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

Сертификат ABS	1SAA963001-0101
Сертификат BV	1SAA963001-0202
Сертификат CB	1SAA963002-2002
CQC Certificate	CQC2010010307387700
Сертификат cUL	cUL_E137861 cUL_E345003
cULus Certificate	cUL_E137861
Declaration of Conformity - CCC	2020980307003526
Декларация о соответствии - CE	1SAD938509-0183
DNV GL Certificate	1SAA963001-0304
EAC Certificate	1SAA963000-2701
Экологическая информация	1SAC200049H0009
Сертификат ГОСТ	1SAA963001-2702
Инструкции и руководства	2CDC131034M6801
Инструкции и руководства (часть 2)	2CDC131060M0202

KC Certificate	1SAA963002-1501
Сертификат LR	1SAA963001-0502
Сертификат RINA	1SAA963002-0802
Сертификат RMRS	1SAA918000-0704
Правила ограничения содержания вредных веществ. RoHS информация	1SAD938505-0183
Time-Current Characteristic Curve	1SAM300515F0001
Сертификат UL	UL_E137861 UL_E345003

Container Information

Package Level 1 Units	1 штука
Package Level 1 Width	92 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	50 mm
Package Level 1 Gross Weight	0.23 kg
Package Level 1 EAN	4013614400179
Package Level 2 Units	40 штука
Package Level 2 Width	280 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Height	210 mm
Package Level 2 Gross Weight	9.586 kg
Package Level 2 EAN	4013614443626

Classifications

Код классификации объекта	F
ETIM 4	EC000074 - Motor protective circuit-breaker
ETIM 5	EC000074 - Motor protective circuit-breaker
ETIM 6	EC000074 - Motor protection circuit-breaker
ETIM 7	EC000074 - Motor protection circuit-breaker
e-класс	V11.0 : 27370401
Универсальная стандартная классификация товаров и услуг (UNSPSC)	39121521
IDEA Granular Category Code (IGCC)	4845 >> 3 Pole Motor Circuit Protector Circuit Breakers
E-Number (Finland)	3705880
E-Number (Sweden)	3110030

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SAM201901R1001	HKF1-11 Auxiliary Contact	HKF1-11	1	piece
1SAM201901R1201	HKF1-11K Auxiliary Contact	HKF1-11K	1	piece
1SAM201901R1002	HKF1-20 Auxiliary Contact	HKF1-20	1	piece
1SAM201901R1202	HKF1-20K Auxiliary Contact	HKF1-20K	1	piece
1SAM201901R1004	HKF1-01 Auxiliary Contact	HKF1-01	1	piece
1SAM201901R1003	HKF1-10 Auxiliary Contact	HKF1-10	1	piece
1SAM201902R1002	HK1-20 Auxiliary Contact	HK1-20	1	piece
1SAM201902R1202	HK1-20K Auxiliary Contact	HK1-20K	1	piece
1SAM201902R1001	HK1-11 Auxiliary Contact	HK1-11	1	piece
1SAM201902R1201	HK1-11K Auxiliary Contact	HK1-11K	1	piece
1SAM201902R1003	HK1-02 Auxiliary Contact	HK1-02	1	piece
1SAM201902R1203	HK1-02K Auxiliary Contact	HK1-02K	1	piece
1SAM201902R1004	HK1-20L Auxiliary Contact	HK1-20L	1	piece
1SAM201902R1204	HK1-20LK Auxiliary Contact	HK1-20LK	1	piece
1SAM201903R1002	SK1-20 Signal Contact	SK1-20	1	piece
1SAM201903R1202	SK1-20K Signal Contact	SK1-20K	1	piece
1SAM201903R1001	SK1-11 Signal Contact	SK1-11	1	piece
1SAM201903R1201	SK1-11K Signal Contact	SK1-11K	1	piece
1SAM201903R1003	SK1-02 Signal Contact	SK1-02	1	piece
1SAM201903R1203	SK1-02K Signal Contact	SK1-02K	1	piece
1SAM201910R1001	AA1-24 Shunt Trip	AA1-24	1	piece
1SAM201910R1002	AA1-110 Shunt Trip	AA1-110	1	piece
1SAM201910R1003	AA1-230 Shunt Trip	AA1-230	1	piece
1SAM201910R1004	AA1-400 Shunt Trip	AA1-400	1	piece
1SAM201904R1010	UA1-20 Undervoltage Release	UA1-20	1	piece
1SAM201904R1001	UA1-24 Undervoltage Release	UA1-24	1	piece
1SAM201904R1002	UA1-48 Undervoltage Release	UA1-48	1	piece
1SAM201904R1003	UA1-60 Undervoltage Release	UA1-60	1	piece
1SAM201904R1004	UA1-110 Undervoltage Release	UA1-110	1	piece
1SAM201904R1008	UA1-208 Undervoltage Release	UA1-208	1	piece
1SAM201904R1005	UA1-230 Undervoltage Release	UA1-230	1	piece
1SAM201904R1006	UA1-400 Undervoltage Release	UA1-400	1	piece
1SAM201904R1007	UA1-415 Undervoltage Release	UA1-415	1	piece
1SAM201904R1009	UA1-575 Undervoltage Release	UA1-575	1	piece
1SAM201906R1102	PS1-2-0-65 Busbar	PS1-2-0-65	1	piece
1SAM201906R1112	PS1-2-1-65 Busbar	PS1-2-1-65	1	piece
1SAM201906R1122	PS1-2-2-65 Busbar	PS1-2-2-65	1	piece
1SAM201916R1103	PS1-3-0-100 Busbar	PS1-3-0-100	1	piece
1SAM201906R1103	PS1-3-0-65 Busbar	PS1-3-0-65	1	piece
1SAM201916R1113	PS1-3-1-100 Busbar	PS1-3-1-100	1	piece
1SAM201906R1113	PS1-3-1-65 Busbar	PS1-3-1-65	1	piece
1SAM201916R1123	PS1-3-2-100 Busbar	PS1-3-2-100	1	piece
1SAM201906R1123	PS1-3-2-65 Busbar	PS1-3-2-65	1	piece
1SAM201916R1104	PS1-4-0-100 Busbar	PS1-4-0-100	1	piece
1SAM201906R1104	PS1-4-0-65 Busbar	PS1-4-0-65	1	piece

1SAM201916R1114	PS1-4-1-100 Busbar	PS1-4-1-100	1	piece
1SAM201906R1114	PS1-4-1-65 Busbar	PS1-4-1-65	1	piece
1SAM201906R1124	PS1-4-2-65 Busbar	PS1-4-2-65	1	piece
1SAM201916R1105	PS1-5-0-100 Busbar	PS1-5-0-100	1	piece
1SAM201906R1105	PS1-5-0-65 Busbar	PS1-5-0-65	1	piece
1SAM201916R1115	PS1-5-1-100 Busbar	PS1-5-1-100	1	piece
1SAM201906R1115	PS1-5-1-65 Busbar	PS1-5-1-65	1	piece
1SAM201906R1125	PS1-5-2-65 Busbar	PS1-5-2-65	1	piece
1SAM201907R1101	S1-M1-25 Power Infeed Block	S1-M1-25	1	piece
1SAM201907R1102	S1-M2-25 Power Infeed Block	S1-M2-25	1	piece
1SAM201907R1103	S1-M3-25 Power Infeed Block	S1-M3-25	1	piece
1SAM201913R1103	S1-M3-35 Power Infeed Block	S1-M3-35	1	piece
1SAM201914R1002	S1-PB1-25 Power Infeed Block	S1-PB1-25	1	piece
1SAM301911R1001	TS1-M3-S1 Terminal Spacer	TS1-M3-S1	1	piece
1SAM301912R1001	TS1-M3-S2 Terminal Spacer	TS1-M3-S2	1	piece
1SAM201914R1001	PB1-1-32 Connecting Link	PB1-1-32	1	piece
1SAM201908R1001	BS1-3 Protection Cover	BS1-3	1	piece
1SAM201909R1001	FS116 Screw Fixing Kit	FS116	1	piece
GJF1101903R0002	SA2 - Terminals and Installation Material	SA2	1	piece
1SAM201911R1012	IB132-F Enclosure	IB132-F	1	piece
1SAM201911R1010	IB132-G Enclosure	IB132-G	1	piece
1SAM201911R1011	IB132-Y Enclosure	IB132-Y	1	piece
1SAM201912R1010	DMS132-G Door Mounting Kit	DMS132-G	1	piece
1SAM201912R1011	DMS132-Y Door Mounting Kit	DMS132-Y	1	piece
1SAM201909R1021	MSAH1 Shaft Supporter	MSAH1	1	piece
1SAM201920R1011	MSHD-LTB Handles	MSHD-LTB	1	piece
1SAM201920R1012	MSHD-LTY Handles	MSHD-LTY	1	piece
1SAM201920R1000	MSH-AR Shaft Alignment Ring	MSH-AR	1	piece
1SAM101923R0002	MSMN Driver	MSMN	1	piece
1SAM101923R0012	MSMNO Driver	MSMNO	1	piece
1SCA101647R1001	OXS6X85 SHAFT	OXS6X85	1	piece
1SCA108043R1001	OXS6X105 SHAFT	OXS6X105	1	piece
1SCA101655R1001	OXS6X130 SHAFT	OXS6X130	1	piece
1SCA101659R1001	OXS6X180 SHAFT	OXS6X180	1	piece

Категории

Низковольтное оборудование → Пускорегулирующая аппаратура → Мотор-автоматы → Мотор-автоматы

Низковольтное оборудование → Силовые автоматические выключатели → Мотор-автоматы

