



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8228-1AD30-2AB1

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Y	ALM 400V	190.0	1,578.0	330.0	390	39.1	1,150	2,750	580.0	4,500	1,578.0	330	0.940	0.910	94.0
	BLM/SLM 400V	165.0	1,576.0	330.0	340	34.1	1,000	2,750	580.0	4,500	1,576.0	330	0.933	0.910	93.0
	ALM/BLM/SLM 480V	218.0	1,542.0	320.0	460	45.7	1,350	2,750	580.0	4,500	1,542.0	320	0.947	0.900	96.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	225
Cooling	Open circuit cooling DE-> NDE
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP23
Design acc. to Code I	IM B3 (IM B6, IM B7, IM B8, IM V6)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft extension	Feather key with half key balancing
Encoder system	Without encoder

Physical constants

Thermal time constant	25 min
Moment of inertia	23,300 kgcm ²
Weight (approx.)	870 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	left
Signal connection	DE
Terminal box designation	1XB7700-P02

Cooling data and sound pressure level

Airflow, min.	0.33 m ³ /s
Sound pressure level LpA(1m) motor + external fan operation 50 HZ rated load, tolerance + 3dB	73 dB ¹⁾
Air discharge	axial
Pressure drop	600 Pa

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 2000 rpm