

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7043-4CH71-1UA0-Z
N05

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data		Mechanical data			
Rated speed (100 K)	4500 rpm	Motor type	Permanent-magnet synchronous motor		
Number of poles	6	Motor type	High Dynamic		
Rated torque (100 K)	2.6 Nm	Shaft height	48		
Rated current	3.3 A	Cooling	Natural cooling		
Static torque (60 K)	2.90 Nm	Radial runout tolerance	0.040 mm		
Static torque (100 K)	3.5 Nm	Concentricity tolerance	0.08 mm		
Stall current (60 K)	3.30 A	Axial runout tolerance	0.08 mm		
Stall current (100 K)	4.10 A	Vibration severity grade	Grade A		
Moment of inertia	1.000 kgcm ²	Connector size	1		
Efficiency	90.0 %	Degree of protection	IP64		
<th colspan="2">Physical constants</th>		Physical constants		Design acc. to Code I	IM B5 (IM V1, IM V3)
		Torque constant	0.85 Nm/A	Temperature monitoring	Pt1000 temperature sensor
		Voltage constant at 20° C	54.0 V/1000*min ⁻¹	Electrical connectors	Connectors for signals and power rotatable
		Winding resistance at 20° C	1.20 Ω	Color of the housing	Standard (Anthracite RAL 7016)
		Rotating field inductance	13.6 mH	Holding brake	without holding brake
		Electrical time constant	11.30 ms	Shaft extension	Feather key
		Mechanical time constant	0.49 ms	Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)
		Thermal time constant	40 min		
		Shaft torsional stiffness	11400 Nm/rad		
		Net weight of the motor	6.0 kg		



Figure similar

MLFB-Ordering data

1FK7043-4CH71-1UA0-Z
N05

Optimum operating point

Optimum speed	4500 rpm
Optimum power	1.2 kW

Limiting data

Max. permissible speed (mech.)	9000 rpm
Max. permissible speed (inverter)	9000 rpm
Maximum torque	10.0 Nm
Maximum current	12.5 A

Recommended Motor Module

Rated inverter current	5 A
Maximum inverter current	15 A
Maximum torque	10.00 Nm

Special design

N05 Non-standard shaft extension (dimensions as for 1FT5 motors)