

Data sheet for SIMOTICS S-1FK7

MLFB-Ordering data

1FK7086-7AF71-1EG0




Figure similar

Client order no. :
 Order no. :
 Offer no. :
 Remarks :

Item no. :
 Consignment no. :
 Project :

Engineering data

Rated speed (100 K)	3000 rpm
Number of poles	8
Rated torque (100 K)	6.5 Nm
Rated current	5.5 A
Static torque (60 K)	23.50 Nm
Static torque (100 K)	28.0 Nm
Stall current (60 K)	17.00 A
Stall current (100 K)	21.00 A
Moment of inertia	23.000 kgcm ²
Efficiency	93.0 %

Physical constants

Torque constant	1.33 Nm/A
Voltage constant at 20° C	85.0 V/1000*min ⁻¹
Winding resistance at 20° C	0.12 Ω
Rotating field inductance	3.0 mH
Electrical time constant	25.00 ms
Mechanical time constant	0.47 ms
Thermal time constant	65 min
Shaft torsional stiffness	83000 Nm/rad
Net weight of the motor	23.5 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	High Dynamic
Shaft height	80
Cooling	Natural cooling
Radial runout tolerance	0.050 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1.5
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Encoder AM2048S/R: absolute encoder 2048 S/R, 4096 revolutions multi-turn, with EnDat interface

MLFB-Ordering data

1FK7086-7AF71-1EG0

Figure similar

Optimum operating point		Recommended Motor Module	
Optimum speed	2000 rpm	Rated inverter current	30 A
Optimum power	3.8 kW	Maximum inverter current	56 A
Limiting data		Maximum torque	72.00 Nm
Max. permissible speed (mech.)	6000 rpm		
Max. permissible speed (inverter)	6800 rpm		
Maximum torque	105.0 Nm		
Maximum current	112.0 A		