

Pointek CLS300 RF Capacitance point level switch, rod design. Detects level and interface in aggressive liquids, solids, slurries, and foam. Adjustable, 1 m (3.28 ft), insertion, adaptable sensitivity, with active shield to tune out build-up on probe. Process Connection: Welded flange, 316L (1.4404) stainless steel, Type A flat faced: DN 25, PN 40 Probe length: (length from flange face) (threaded lengths include process thread) Standard version, rod 350 mm (13.78") Thermal Isolator: With thermal isolator (for process connection temperatures over +85 C (+185 F)) Wetted Seals: FKM Probe Material: 316L Stainless Steel with PFA lining and PEEK Isolators Approvals: Explosion Proof Enclosure With IS Probe: CSA/FM Class I, Div. 1, Gr. A, B, C, D CSA/FM Class II, Div. 1, Gr. E, F, G CSA/FM Class III T4 Enclosure and Lid: Aluminum epoxy coated 2 x 1/2" NPT via adapter - cable inlet, IP65 Active Shield Length: Standard length - (125 mm threaded, 105 mm flanged)

## Further information

Industry Online Support (Manuals, Catalogs, Certificates, FAQ, ...)

<https://support.industry.siemens.com/cs/products?mf=ps&lc=en-WW>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com>

