

Data sheet for SIMOTICS S-1FK7

No image available for this configuration.

MLFB-Ordering data

1FK7042-5AK71-1FB3

Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Engineering data

Rated speed (100 K) 6000 rpm

Number of poles 8

Rated torque (100 K) 1.5 Nm

Rated current 2.5 A

Static torque (60 K) 2.50 Nm

Static torque (100 K) 3.0 Nm

Stall current (60 K) 3.60 A

Stall current (100 K) 4.40 A

Moment of inertia 3.450 kgcm²

Efficiency 89.0 %

Physical constants

Torque constant 0.69 Nm/A

Voltage constant at 20° C 44.0 V/1000*min⁻¹

Winding resistance at 20° C 1.20 Ω

Rotating field inductance 6.7 mH

Electrical time constant 5.60 ms

Mechanical time constant 2.27 ms

Thermal time constant 30 min

Shaft torsional stiffness 16000 Nm/rad

Net weight of the motor 5.4 kg

Mechanical data

Motor type Permanent-magnet synchronous motor

Motor type Compact

Shaft height 48

Cooling Natural cooling

Radial runout tolerance 0.040 mm

Concentricity tolerance 0.08 mm

Axial runout tolerance 0.08 mm

Vibration severity grade Grade A

Connector size 1

Degree of protection IP64

Design acc. to Code I IM B5 (IM V1, IM V3)

Temperature monitoring KTY84 temperature sensor in the stator winding

Electrical connectors Connectors for signals and power rotatable

Color of the housing Standard (Anthracite RAL 7016)

Holding brake with holding brake

Shaft end Feather key

Encoder system Encoder AM22DQ: absolute encoder 22 bits (resolution 4194304, encoder-internal 2048 S/R) + 12 bits multi-turn (traversing range 4096 revolutions)

MLFB-Ordering data

1FK7042-5AK71-1FB3

Figure similar

Optimum operating point

Optimum speed	5000 rpm
Optimum power	1.0 kW

Limiting data

Max. permissible speed (mech.)	9000 rpm
Max. permissible speed (inverter)	9990 rpm
Maximum torque	10.5 Nm
Maximum current	15.3 A

Holding brake

Holding brake version	Permanent-magnet brake
Holding torque	4.0 Nm
Power supply voltage	DC 24 V \pm 10 %
Coil current	0.5 A
Opening time	70 ms
Closing time	30 ms
Highest braking work	150 J

Recommended Motor Module

Rated inverter current	5 A
Maximum inverter current	10 A
Maximum torque	6.80 Nm