

Switch disconnecter with fuses

Model	
product designation	switch disconnecter with fuses
design of the product	for NH 0
fuse system	NH 0
Supply voltage	
operating voltage / at DC / rated value	220 V
Protection class	
protection class IP	IP00
Main circuit	
operational current / rated value	125 A
suitability for use	
• safety switch	Yes
Connections	
type of electrical connection / for main current circuit	BUSBAR CONNECTION
Mechanical Design	
height	147 m
width	168 m
depth	94.5 m
fastening method	Surface mounting and installation
net weight	1.9 kg
Environmental conditions	
ambient temperature / during operation	
• minimum	-20 °C
• maximum	45 °C
ambient temperature / during storage / minimum	-25 °C
General Product Approval	
	other



[Miscellaneous](#)

[Environmental Con-
firmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3KL7122-3AA00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3KL7122-3AA00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3KL7122-3AA00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



