

Data sheet for SIMOTICS S-1FK7



Figure similar

MLFB-Ordering data

1FK7060-5AH71-1UG0

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

Rated speed (100 K)	4500 rpm
Number of poles	8
Rated torque (100 K)	3.7 Nm
Rated current	4.1 A
Static torque (60 K)	5.00 Nm
Static torque (100 K)	6.0 Nm
Stall current (60 K)	5.10 A
Stall current (100 K)	6.20 A
Moment of inertia	7.950 kgcm ²
Efficiency	90.0 %

Physical constants

Torque constant	0.95 Nm/A
Voltage constant at 20° C	60.5 V/1000*min ⁻¹
Winding resistance at 20° C	0.73 Ω
Rotating field inductance	7.0 mH
Electrical time constant	9.60 ms
Mechanical time constant	1.93 ms
Thermal time constant	30 min
Shaft torsional stiffness	42000 Nm/rad
Net weight of the motor	7.0 kg

Mechanical data

Motor type	Permanent-magnet synchronous motor
Motor type	Compact
Shaft height	63
Cooling	Natural cooling
Radial runout tolerance	0.040 mm
Concentricity tolerance	0.10 mm
Axial runout tolerance	0.10 mm
Vibration severity grade	Grade A
Connector size	1
Degree of protection	IP64
Design acc. to Code I	IM B5 (IM V1, IM V3)
Temperature monitoring	KTY84 temperature sensor in the stator winding
Electrical connectors	Connectors for signals and power rotatable
Color of the housing	without
Holding brake	without holding brake
Shaft end	Plain shaft
Encoder system	Resolver R15DQ: resolver 15 bits (resolution 32768, internal multi-pole)

MLFB-Ordering data

1FK7060-5AH71-1UG0

Figure similar

Optimum operating point

Optimum speed 4500 rpm

Optimum power 1.7 kW

Limiting data

Max. permissible speed (mech.) 7200 rpm

Max. permissible speed (inverter) 9500 rpm

Maximum torque 18.0 Nm

Maximum current 19.5 A

Recommended Motor Module

Rated inverter current 9 A

Maximum inverter current 18 A

Maximum torque 16.80 Nm