

Modlight Illumix Classic Line 24W


LED machine lamp, IP67, 24VDC, M12 connection

Modlight Illumix Classic Line

24 W

Link to Product

Illustration



Product may differ from Image



Technical Data

Operating voltage	24 V DC (21.6...27.6 V DC)
No. of poles	4-pole
Coding	A-coded
Connection	M12 (male)
Luminaire light yield	approx. 105 lm/W
Luminaire light current	approx. 2520 lm
Color reproduction (Ra)	> 80
Light color	Daylight white, approx. 5500 K
Lighting angle	> 120°
Input current	24 W

General data

Mounting method	rotatable
Temperature range	-30...+50 °C
Material (housing)	Anodized aluminum
Material (light cover)	diffuse single-pane safety glass (ESG), 4 mm
Installation altitude	Operation up to 2 000 m
Vibration stress	2...9 Hz/10 mm; 9...200 Hz/3 g
Screw head-Ø	max. 12 mm/M5
Relative humidity	5...95%
Protection	IP67
Dimensions H×W×D	37×760×40 mm (1.46×29.92×1.57 in)
Shock load	50 g, 11 ms

Commercial data

country of origin	DE
customs tariff number	94054239
EAN	4048879670838

eClass	27110306
Packaging unit	1.000
