

**Modlink MSDD-set: Frame 4000-68122-000000,**  
insert 4000-68000-0250000 + 4000-68000-0040000

### [Link to Product](#)

#### Illustration



Product may differ from Image

#### Frame

The information in this brochure has been compiled with the utmost care.  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

suitable for mounting with wall thickness	1...5 mm
Protection	IP65
Housing	Zinc die-casting, KTL coated
Temperature range	-10...+60 °C (storage temperature -25...+60 °C)

**SUB-D9**

Operating voltage	48 V AC/DC
Operating voltage (UL Rating)	max. 30 V AC/42.4 V DC
Operating current	3 A
Operating current (UL Rating)	max. 175 mA
No. of poles	9-pole
Connection front side	SUB-D (female)
Connection rear side	SUB-D (female)
Locking of ports	UNC 4...40 bolt

**USA**

Operating voltage	125 V AC
Operating current	15 A
No. of poles	2 + PE
Connection	Screw terminals: max. 2× 2.5 mm <sup>2</sup> (AWG 14)

**Commercial data**

country of origin	CZ
customs tariff number	85389099
EAN	4048879035668
eClass	27189217
Packaging unit	1