



### Main

Range of product	TeSys
Product name	LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay to be ordered separately Contactor
[Ie] rated operational current	18 A AC-3
Motor power kW	7.5 kW at 380/400 V AC 50/60 Hz 9 kW at 440 V AC 50/60 Hz 9 kW at 415 V AC 50/60 Hz 4 kW at 220/230 V AC 50/60 Hz 10 kW at 660/690 V AC 50/60 Hz 10 kW at 500 V AC 50/60 Hz
[I <sub>th</sub> ] conventional enclosed thermal current	18 A
[U <sub>c</sub> ] control circuit voltage	115 V AC 50/60 Hz
Control type	Pushbutton stop/reset red O Pushbutton start green I

### Complementary

Cable entry number	2 cable entry :ISO25 bottom 2 cable entry :Pg 21 bottom 2 cable entry :ISO25 top 2 cable entry :Pg 16 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO20 top
Width	101 mm
Height	201 mm
Depth	153.5 mm
Product weight	1.015 kg

### Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0817 - <a href="#">Schneider Electric declaration of conformity</a>
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.