

Main

| | |
|--|--|
| Range of product | TeSys |
| Product name | LE |
| Device short name | LE1D |
| Product or component type | Enclosed DOL starter |
| Device application | Standard |
| Utilisation category | AC-3 |
| Device composition | Thermal overload relay to be ordered separately Contactor |
| [Ie] rated operational current | 18 A AC-3 |
| Motor power kW | 7.5 kW at 380/400 V AC 50/60 Hz 9 kW at 440 V AC 50/60 Hz 9 kW at 415 V AC 50/60 Hz 4 kW at 220/230 V AC 50/60 Hz 10 kW at 660/690 V AC 50/60 Hz 10 kW at 500 V AC 50/60 Hz |
| [Ithe] conventional enclosed thermal current | 18 A |
| [Uc] control circuit voltage | 415 V AC 50/60 Hz |
| Control type | Selector switch 2 positions start/stop O-I Pushbutton reset blue R |

Complementary

| | |
|--------------------|--|
| Cable entry number | 2 cable entry :ISO25 bottom 2 cable entry :Pg 21 bottom 2 cable entry :ISO25 top 2 cable entry :Pg 16 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO20 top |
| Width | 101 mm |
| Height | 201 mm |
| Depth | 160 mm |
| Product weight | 1.015 kg |

Environment

| | |
|---------------------------------------|------------------------------|
| Material | Polycarbonate |
| IP degree of protection | IP65 conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529 |
| Standards | IEC 60947-4-1 |
| Ambient air temperature for operation | -5...40 °C |