



### Main

Range	TeSys
Product name	TeSys LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Contacteur Thermal overload relay to be ordered separately
[Ie] rated operational current	25 A AC-3
Motor power kW	5.5 kW at 220/230 V AC 50/60 Hz 15 kW at 660/690 V AC 50/60 Hz 15 kW at 500 V AC 50/60 Hz 11 kW at 440 V AC 50/60 Hz 11 kW at 415 V AC 50/60 Hz 11 kW at 380/400 V AC 50/60 Hz
[Ith] conventional enclosed thermal current	25 A
[Uc] control circuit voltage	230 V AC 50/60 Hz
Control type	Push-button stop/reset red O Push-button start green I

### Complementary

Cable entry number	2 cable entry :ISO25 bottom 2 cable entry :Pg 21 bottom 2 cable entry :ISO25 top 2 cable entry :Pg 16 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO20 top
Width	101 mm
Height	201 mm
Depth	153.5 mm
Product weight	1.015 kg

### Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0817 - <a href="#">Schneider Electric declaration of conformity</a>
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations