

Modlink MSDD set contains:Frame 4000-68512-0000003

Insert 4000-68000-4620004

Link to Product

Illustration



Product may differ from Image

Frame

| | |
|---|--|
| suitable for mounting with wall thickness | 1...5 mm |
| Protection | IP65 |
| Temperature range | -30...+70 °C (storage temperature -30...+80 °C) |
| Housing | Frame: plastic PA black, cap: plastic PC transparent |

RJ45

| | |
|-------------------------------|---------------------------------------|
| Operating current (UL Rating) | max. 175 mA |
| Locking of ports | Snap In |
| Connection front side | RJ45 |
| Connection rear side | RJ45 |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |
| Specification | CAT5e, Class D, 100 MHz, (EN 50173-1) |

USB

| | |
|-------------------|-------|
| Operating current | 1.5 A |
|-------------------|-------|

| | |
|-------------------------------|--------------------------|
| Specification | USB: 3.0 (max. 5 Gbit/s) |
| Locking of ports | Snap In |
| Operating voltage | 48 V AC/DC |
| Operating voltage (UL Rating) | max. 30 V AC/42.4 V DC |

Shielding plate

| | |
|-------------------|------------------|
| Tightening torque | 0.9 Nm \pm 0.1 |
| Connection | Threaded hole M4 |

Commercial data

| | |
|-----------------------|---------------|
| country of origin | LV |
| customs tariff number | 85366990 |
| EAN | 4048879862660 |
| Packaging unit | 1.000 |