

## DRIVE CLIQ CABLE

Specification: 6FX2002-1DC00-1AD0


DRIVE-CLiQ-System  
Male straight – male straight

Further cable lengths on request.

The resistance to aggressive media should be individually tested for your application. Further details on request.

### Link to Product


#### Illustration



Male



Male



Product may differ from Image

#### Form

Form SS021

#### Technical Data

Operating voltage	max. 30 V AC/DC
Rated surge voltage	0.5 kV
Operating current	max. 1.76 A
Material group	IEC 60664-1, category II
Locking of ports	DRIVE-CLiQ-System
Protection	IP20

#### General data

Pollution Degree	3
Temperature range	-20...+80 °C, depending on cable quality

#### Cables

No./diameter of wires	2x 2x 0.22 mm <sup>2</sup>
Wire isolation	PE (gn, ye, pk, bl)
Outer Ø	6.9 mm ±5%
Cable number	884
Shield	yes
Jacket Color	gray
Temperature range (fixed)	-20...+80 °C
Temperature range (mobile)	0...+60 °C

The information in this brochure has been compiled with the utmost care.  
Liability for the correctness completeness and topicality of the information is restricted to gross negligence. Version: 03/22

Bend radius (fixed)	7.5× outer Ø
Bend radius (moving)	15× outer Ø
Material (jacket)	PVC (UL/CSA)
<b>Commercial data</b>	
country of origin	DE
customs tariff number	85444210
EAN	4048879679763
eClass	27061801
Packaging unit	1.000