

Main

Range	TeSys
Product name	TeSys LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Contactors Thermal overload relay to be ordered separately
[Ie] rated operational current	50 A AC-3
Motor power kW	33 kW at 660/690 V AC 50/60 Hz 30 kW at 500 V AC 50/60 Hz 30 kW at 440 V AC 50/60 Hz 25 kW at 415 V AC 50/60 Hz 22 kW at 380/400 V AC 50/60 Hz 15 kW at 220/230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	50 A
[Uc] control circuit voltage	230 V AC 50/60 Hz
Control type	Push-button stop/reset red O Push-button start green I

Complementary

Cable entry number	3 cable entry :1 ISO20 + 2 ISO32 bottom 1 cable entry :ISO32 top
Width	200 mm
Height	300 mm
Depth	158.4 mm
Product weight	4.85 kg

Environment

Material	Sheet steel
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C