



### Main

Range of product	TeSys
Product name	LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Fuse disconnecter Thermal overload relay ordered separately Reversing contactor
[Ie] rated operational current	40 A AC-3
Motor power kW	18.5 kW at 380/400 V AC 50/60 Hz 30 kW at 660/690 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 22 kW at 440 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 11 kW at 220/230 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	40 A
Associated fuse rating	40 A 14 x 51 mm aM
Control type	Without

### Complementary

Cable entry number	2 cable entry :1 Pg 13 + 1 Pg 21 top 3 cable entry :1 ISO20 + 2 ISO25 bottom 3 cable entry :1 Pg 13 + 2 Pg 21 bottom 2 cable entry :1 ISO20 + 1 ISO25 top
Width	300 mm
Height	325 mm
Depth	218 mm
Product weight	14.17 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C