

### Main

Range of product	TeSys
Product name	LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Fuse disconnecter Thermal overload relay ordered separately Reversing contactor
[Ie] rated operational current	80 A AC-3
Motor power kW	55 kW at 500 V AC 50/60 Hz 45 kW at 660/690 V AC 50/60 Hz 45 kW at 440 V AC 50/60 Hz 45 kW at 415 V AC 50/60 Hz 37 kW at 380/400 V AC 50/60 Hz 22 kW at 220/230 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
[Ith] conventional enclosed thermal current	80 A
Associated fuse rating	80 A 22 x 58 mm aM
Control type	Without

### Complementary

Cable entry number	3 cable entry :1 ISO20 + 2 ISO40 bottom 3 cable entry :1 Pg 13 + 2 Pg 36 bottom 2 cable entry :1 ISO20 + 1 ISO40 top 2 cable entry :1 Pg 13 + 1 Pg 36 top
Width	400 mm
Height	325 mm
Depth	218 mm
Product weight	16 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.